


ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS				DOC. NO. SPC-F004 * Effective: 12/21/98 * DCP No: 680					
DCP #	REV	DESCRIPTION		DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
948	A	RELEASED		HYD	7/12/00	JC	10/18/00	DJC	10/18/00



SPECIFICATIONS:

1. Volts: 12.8/14
2. AMPS: 2.1/0.59
3. Watts: 26.88/8.26
4. MSCP: 32/3
5. Filament: C-6/C-6
6. Life: 600/5000+

SPC-F004.DWG

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.



SPC TECHNOLOGY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
HISHAM ODISH	7/12/00
CHECKED BY:	DATE:
JOHN COLE	10/18/00
APPROVED BY:	DATE:
DANIEL CAREY	10/18/00

DRAWING TITLE:

S-8 DOUBLE CONTACT INDEX BASE LAMP

SIZE DWG. NO.

A

1157

ELECTRONIC FILE

96F7955.DWG

REV

A

SCALE: NTS

U.O.M.: INCHES

SHEET: 1 OF 1