



TECHNICAL CHARACTERISTICS

MATERIAL
 INSULATOR: NYLON 66
 COLOR: GREEN
 METAL HOUSING: BRASS (CuZn)
 TERMINAL SCREW: STEEL ZINC PLATING "-" SLOT TYPE
 WIRE GUARD: PhBz TIN PLATED

ENVIRONMENTAL
 OPERATING TEMPERATURE: -30 UP TO 105°C
 FLAMABILITY RATING: UL94-V0
 COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL	cULus	VDE
CURRENT RATING:	10A	10.5A
WORKING VOLTAGE:	300VAC	300VAC
WITHSTANDING VOLTAGE:	1.6KV	2.5KV

MECHANICAL		
SOLID WIRE:	16-26 AWG	1.5MM ²
STRANDED WIRE:	16-26 AWG	1.5MM ²
TORQUE :	3.0Lb.In	0.2Nm

WIRE STRIPE LENGTH: 6-7MM
 SCREW: M2
 PITCH: 3.81MM

SOLDERING: WAVE PROCESS ONLY

PACKAGING
 BOX

SERIE 361

CERTIFICATION



RoHS Compliant

G			
F			
E			
D			
C			
B			
A	31-OCT-07	PDF	EC
REV	DATE	FILE	BY

PROJECTION:

GENERAL TOLERANCE
 .X = +/- 0.2
 .XX = +/- 0.15

APPROVAL: RJ

UNIT: MM
 SCALE:
 SHEET: 1/1
 DRAW: MARVIN

DESCRIPTION: 3.81MM GREEN PLUG VERTICAL CABLE ENTRY WITH SCREW
 WERI PART NO: 691 361 300 0xx

SIZE
A4