



Model No.	POS.1	POS.2	POS.3
	1MS4 Term. Comm.	MOM	OFF
SCHEMATIC	2-3 	OPEN	2-1

SWITCH FUNCTION

PANEL MOUNTING

P.C. MOUNTING

SPECIFICATIONS
ELECTRICAL LIFE: 40,000 make-and-break cycles at full load.
CONTACT RESISTANCE: 10m Ω max. initial @ 2-4VDC
 100mA for both silver and gold plated contacts.
INSULATION RESISTANCE: 1,000M Ω min.
DIELECTRIC STRENGTH: 1,000 V RMS@sea level.
OPERATING TEMPERATURE: -30° C to 85° C.

MATERIALS
CASE: Dially phthalate (DAP) (UL94v-0).
ACTUATOR: Brass,chrome plated.
BUSHING: Brass,nickel plated.
HOUSING: Stainless Steel.
TERMINAL/CONTACT: Silver or gold plated.
SWITCH SUPPORT: Brass, Tin plated.

RATING :

R : 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)
 Q : 2Amps @250VAC
 5Amps @120 VAC or 28 VDC

符號	原尺寸	修改後尺寸	變更日期
1 (A)			
2 (B)			
3 (C)			
4 (D)			
5 (E)			

SCALE (比例) : 3 : 2		TITLE	圖名	Miniature Toggle Switches	SIZE	圖紙	A4
TOLERANCE (公差) :		DWG NO.	1MS4T2B4M6RE		UNIT	英寸	mm
0.00 mm \pm 0.25mm		REV.	A	DATE	MAY - 26 - 2003	SHEET	1 of 1
0.0 mm \pm 0.40mm		CHECKED BY	JACK	DRAWN BY	BLUE		
ANGULAR : \pm 2.54 mm		審核		製圖			
FILE NAME : 1MSP0385							

德利威電子股份有限公司
DAILYWELL ELECTRONICS CO.,LTD.