



Model No.	POS.1	POS.2	POS.3
ZAS5	ON	OFF	MOM
Term. Comm.	2-3	OPEN	2-1
SCHEMATIC			

SWITCH FUNCTION

**SPECIFICATIONS**

**ELECTRICAL LIFE:** 50,000 make-and-break cycles at full load.  
**CONTACT RESISTANCE:** 20m Ω max. Initial @ 2-4VDC  
 100mA for both silver and gold plated contacts.  
**INSULATION RESISTANCE:** 1,000M Ω min.  
**DIELECTRIC STRENGTH:** 1,000 V RMS@sea level.  
**OPERATING TEMPERATURE:** -30° C to 85° C.

**MATERIALS**

**CASE & BUSHING -** Glass filled nylon 6/6, retardant, heat stadiized( UL94V-0 )  
**ACTUATOR -** Brass, chrome plated, Internal O-ring seal, standard for all actuators.  
**SWITCH SUPPORT -** Brass, tin plated.  
**TERMINALS/CONTACT -** Silver or gold plated copper.

**RATING :**

R : 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)  
 Q : 1Amp @250VAC  
 3Amps @120 VAC or 28 VDC

符號	原尺寸	修改後尺寸	變更日期
1	(A)		
2	(B)		
3	(C)		
4	(D)		
5	(E)		

SCALE (比例) :	3 : 2
TOLERANCE (公差) :	0.00 mm ± 0.25mm
ANGULAR :	± 2.54 mm
FILE NAME :	2ASPP0066

TITLE 圖名	Sealed Sub - Miniature Toggle Switches <th>SIZE 圖紙</th> <td>A4</td>	SIZE 圖紙	A4
DWG NO. 圖號	2AS5T2A1M6RE	UNIT 單位	inch mm
REV. 版本	A	DATE 日期	MAY - 26 - 2003
CHECKED BY 審核	Jack	DRAWN BY 製圖	BLUE
SHEET 張數	1 of 1		

**德利威電子股份有限公司**  
**DAILYWELL ELECTRONICS CO.,LTD.**