



TECHNICAL SPECIFICATION

Technical Service Department,
JSP Ltd., Worsham Mill, Minster
Lovell, Oxford, OX29 0TA
Tel.: 01993 824000
Fax: 01993 824422

Retractaspec

- Conformity:** Meets the requirements of EN 166.
EC Type Examination Certificate Number 52231, issued by BSi
Product Certification, in accordance with the PPE Directive
89/686/EEC.
- Performance:** Eyeshield offers protection against low energy high speed particles at
45 m/s (101 mph). The optical qualities of the lens comply with the
requirements of optical class 1 (highest).
Markings: EN166 1.F
- Materials:** PVC Nose Bridge
Nylon Fittings
Acetate Eye Shield (Optional Anti Glare)
- Instructions For Use:** In use ensure that the Eyeshield is fitted to a helmet.
Ensure that the Eyeshield is in place, before entering the hazard area.
- Cleaning & Maintenance:** Rinse in a 1% solution of mild detergent and dry with a soft cloth.
DO NOT USE abrasive substances or solvents.
Store in the packaging provided, out of direct sunlight, away from
chemical and abrasive substances.
If the Eyeshield becomes scratched or damaged they should be
replaced.
- Limitations Of Use:** The Eyeshield, when in contact with the skin may cause allergic
reactions to susceptible individuals. If this occurs leave the hazard
area, remove the Eyeshield and seek medical advice.
- This Eyeshield is not suitable for protection against dusts, liquids or
molten metals.