



HOME | DISTRIBUTORS | ABOUT US

 SEARCH
Advanced

DC Power Supplies : Triple Output Power Supply

Model No. 72-6615



Features:

- Two independently adjustable 0 to 30VDC regulated power supplies plus a 5VDC (fixed) power supply
- Fine and coarse adjustments for accurate voltage and current settings
- Auto tracking
- Selectable independent, series and parallel operation
- Constant voltage and constant current operation
- Analog meter reading of voltage and current for each 30V supply
- Overload and reverse polarity protection
- Power requirements: 100V, 120V, 220V, 240VAC, 50/60Hz
- Includes test leads and owners manual

Analyzers

Spectrum Analyzers

Audio

Audio Generators
Dummy Loads
Sound Level Meters

Cable Testers

Break Out Boxes
PC Cable

Counters

Frequency
Handheld Frequency
Universal

Engine Analyzers

Engine Analyzers

Hand Tools

SMD Tweezers

Meters

AC Clamp On
AC Millivolt
Anemometers
Capacitance
Clamp Adaptors
Current Loop
Calibrators
DMMs
ESR Meters
Holsters
LCR
Light
Mini AC Clamp
Moisture
Pen DMM
Photo Tachometers
Temperature
Thermo
Anemometers
VOMs

Oscilloscopes

Cases
Handheld
Oscilloscope Cases
Probes
Scopes
Spectrum Analyzer
Adapters

Power

DC Power Supplies
High Current
Isolated AC
Isolation
Transformers
Lab Power Supplies

Specifications	
Voltage (each 30V supply)	Adjustable from 0~30VDC
Line and load regulation	≤0.01% + 3mV
Ripple and noise	≤1mV RMS
Current (each 30V supply)	Adjustable from 0~3A
Line and load regulation	≤0.2% + 3mA
Ripple current	≤3mA RMS
5V supply regulation	Line: ≤5mV, Load: ≤10mV
Ripple and noise	≤2mV RMS
Output current	3A max.
Dimensions/weight	10" (W) x 5 3/4" (H) x 13 1/4" (D)/24 lbs.