



E I DUPONT DE NEMOURS & CO INC
 DUPONT POLYMERS, ENGINEERING POLYMERS
 NYLON RESINS PO BOX 80713, CHESTNUT RUN
 PLAZA, WILMINGTON DE 19880

E41938 (M)



Mtl Dsg	Col	Min Thk mm	UL94 Flame Class	Elec	RTI		H W	H A	H V	D 4	C	
					with Imp	w/o Imp						
Polyamide, Type 66 nylon (PA66), designated "Zytel", furnished in the form of pellets.												
132F.	All	0.71	94V-2	125	65	65	4	0	—	—	—	
133L 135F	All	1.5	94V-2	125	75	85	3	0	0	—	—	
		3.0	94V-2	125	75	85	2	0	0	6	0	
		6.0	94V-2	125	75	85	2	0	0	—	—	
101(f2), 101F, 101L, E101L, E101(f1)	All	0.71	94V-2	125	65	65	4	0	—	—	—	
		1.5	94V-2	125	75	85	3	0	0	—	—	
101(f2), 101F, 101L, E101L, E101(f1)	All	3.0	94V-2	125	75	85	2	0	0	6	0	
		6.0	94V-2	125	75	85	2	0	0	—	—	
EFE1068	All	0.71	94V-2	125	65	65	4	0	—	—	—	
		1.5	94V-2	125	75	85	3	0	0	—	—	
		3.0	94V-2	125	75	85	2	0	0	6	0	
		6.0	94V-2	125	75	85	2	0	0	—	—	
EFE1030	All	0.71	94V-2	125	—	—	4	0	—	—	—	
		1.5	94V-2	125	75	85	3	0	0	—	—	
		3.0	94V-2	125	75	85	2	0	0	6	0	
		6.0	94V-2	125	75	85	2	0	0	—	—	
FE-3370	NC. GY	0.84	94HB	65	65	65	—	—	—	—	—	
FE-3397	NC. GY	0.85	94HB	65	65	65	—	—	—	—	—	

3009312

TOLERANCE: L ≤ 10 ±0.2 10 < L ≤ 30 ±0.3 30 < L ≤ 50 ±0.5 50 < L ≤ 100 ±0.7 100 < L ≤ 250 ±1.2 ABOVE 250 ±1.5	APPROVED BY	張道陽	87.8.26.	 品固企業有限公司 品基電子塑膠製品廠 PINGOOD ENTERPRISE CO., LTD.	PART NAME: LED 座 LED HOUSING	REV. A SIZE 1
	REVIEWED BY	蕭存桂	87.8.26.			
	DRAWN BY	蕭存桂	87.8.26.			
	MATERIAL: NYLON 66(UL) FLAME CLASS: 94V-2 COLOR: NATURAL					
 UNIT mm	SCALE					