











Soldering tips for LR 21, LR 21 antistatic, T 3001, EC 1201 (ET-Series)

Model	Description	Width A	Thickness B	Order-No. for regular solder	Order-No. for HMP- solder
ET-H	 <p>Chisel</p>	0,8 mm	0,4	5 41 000 99	5 41 000 74
ET-A		1,6 mm	0,7	5 41 001 99	-
ET-B		2,4 mm	0,8	5 41 002 99	5 41 002 71
ET-C		3,2 mm	0,8	5 41 003 99	5 41 003 72
ET-D		4,6 mm	0,8	5 41 004 99	-
ET-E		5,6 mm	1,2	5 41 005 99	-
ET-K	 <p>long form</p>	1,2 mm	0,4	5 41 006 99	-
ET-L		2,0 mm	1,0	5 41 007 99	5 41 007 73
ET-M		3,2 mm	1,2	5 41 008 99	-
ET-BS	 <p>Round tip, blunt</p>	2,4 mm		5 41 009 99	-
ET-CS		3,2 mm		5 41 010 99	-
ET-DS		5,0 mm		5 41 011 99	-
ET-F	 <p>Round tip, sloped</p>	1,2 mm		5 41 012 99	-
ET-BB		2,4 mm		5 41 055 99	-
ET-CC		3,2 mm		5 41 013 99	-
ET-O	 <p>Longform, conical</p>	0,8 mm		5 41 014 99	-
ET-S		0,4 mm		5 41 017 99	-
ET-R	 <p>Chisel</p>	1,6 mm	0,7	5 41 015 99	-
ET-MX	 <p>Chise, bent, one side wettable only</p>	3,2 mm	1,2	5 41 016 99	-
ET calibration tip				5 24 750 00	
ET-SMD Chip soldering/ ET-SMD desoldering tip		2,5 x 1,5 mm 3,8 x 1,5 mm		5 41 039 99 5 41 040 99	- -
	Einschraubspitze Außengewinde = M5			5 41 703 00	
	 <p>Tool for tip exchange</p>			5 87 060 43	