

Specification:

Dielectric Withstand	1000V dc
Max. Working Current	2A @ 12V ac/dc
Insulation Resistance	10 ³ MΩ @ 500V dc
Operating Temperature	-20° to +70°C
Endurance	10,000 insertions

Materials:

Body & Cap	Nickel plated Brass
Contacts	Silver plated Phosphor Bronze
Insulating Sleeves	ABS
Contact Base	Polyamide
Cable Clamp	Polypropylene


Compatible With:

Schurter Plugs	4803.1200, 4803.1210 & 4803.1220
Other Plugs	EIAJ RC-6701A

Suitable Cable:

Conductor	0.2mm ² stranded eg. 7/0.2mm or 24 AWG
Overall Diameter	Ø5.5 max.

Schematic Diagram



ISS.	MOD. & DATE		TOLERANCES XX +/- 0.4 XXX +/- 0.1 UNLESS STATED OTHERWISE	MATL. See above	SCALE 1.5 x FULL SIZE DO NOT SCALE DRAWING	TITLE Line Socket 6.35mm, 2 Pole, Screened, Metal Cap
1	15.5.01			FINISH See above	USED ON:	
2	21.11.01					DRG No. 4803.3200
			DIMS IN MM	SCHURTER LTD.	BOGNOR REGIS, UNITED KINGDOM	SHT. 1 OF 1 SHTS.