

Features:

- * Universal AC Input 90—264Vac
- * Low ripple & noise
- * No minimum load requirement
- * 100% burn in test
- * 1 year warranty
- * Safety: GS, CB, CE
- * RoHS Compliant
- * CEC Compliant



SPECIFICATION:

MODEL NO.	3A-041WT-05	3A-041WT-09	3A-041WT-12				
PART NO.	T4113ST	T4114ST	T4115ST				
OUTPUT:							
Voltage	5.0VDC	9.0VDC	12.0VDC				
Current (Max)	1.0A	0.55A	0.42A				
Current (Min)	0A						
Line Regulation	+/-1%						
O/P Voltage Tolerance	+/-5%	+/-5%	+/-5%				
Over Voltage Protection	Zener Clamped O/P Shutdown						
Short Circuit Protection	O/P Shutdown Auto Restart						
Ripple Voltage (L.F)	100mV P-P	100mV P-P	120mV P-P				
O/P Connector (1.5M Jack Lead)	2.1x5.5x12mm Centre +VE R/A						
SAFETY:							
Hi Pot Test I/P-O/P	3KVAC or 4242VDC						
Insulation I/P-O/P	100Mohm						
TEMPERATURE:							
Operating	0 to 40°C						
Storage	-10 to 70°C						
HUMIDITY:							
Operating	20 to 80% Non Condensing						
Storage	10 to 90% Non Condensing						
INPUT:							
Voltage	90 to 264VAC						
Frequency	47 to 63Hz						
Current RMS (Max)	200mA						
Inrush Current	15A/30A						
Leakage Current	0.25mA						
Efficiency (Min) Average	64.5% CEC Compliant	64.5% CEC Compliant	64.5% CEC Compliant				
I/P Power (No Load)	<0.3W CEC Compliant	<0.3W CEC Compliant	<0.3W CEC Compliant				
MTBF	50K Hours						
Safety	EN 60950-1,	IEC 60950-1,	UL 60950-1,	CSA C22.2	No. 60950-1		
Additional Safety							
EMI	FCC CFR 47 PART 15,		EN 55022,	EN 61000-3			
EMC	EN 55024 (EN61024-3),		EN 61000-4				

1 ARKWRIGHT ROAD, READING, BERKS. RG2 0LU

TEL: 0118 9311199

FAX: 0118 9311145

E-Mail: info@stontronics.co.uk www.stontronics.co.uk

Dimensions:

Weight: 85g Approx.

