



COMPACT, DATA ENTRY KEYBOARD

G81-1800



Available Part Numbers

- G81-1800HBAUS** 101 Keys, Black, AT
- G81-1800HQAUS** 101 Keys, Black, PS/2
- G81-1800LAAUS-0** 101 Keys, Light Grey, AT
- G81-1800LAMUS-0** 104 Keys, Light Grey, AT
- G81-1800LPAUS-0** 101 Keys, Light Grey, PS/2
- G81-1800LPMUS-0** 104 Keys, Light Grey, PS/2

Colors

Light Grey, Black

Dimensions

L x W x H = 16.0" x 7.1" x 1.45"

Keys

101 Keys
104 Key Windows Compatible
Laser Printed - Light Grey
Two Shot Molded - Black

Keyswitch Technology

FTSC - Full Travel Sealed Contact & Membrane

Interfaces

AT , PS/2

Optional Features

Multiple Languages Available

Power Supply

+5V/DC \pm 5%, 35mA typical

Temperature

Storage Range: -4°F to +140°F
Operating Range: +32°F to +122°F

Reliability

MCBF: 1 x 10⁹ operations
MTBF: > 80, hours; Operating Life of Individual
Keys: Up to 50 million actuations



FCC Part 15 Subpart
B Class B

CISPR 22 EN 550 22

Cherry Electrical Products

Phone: 800 510 1689
Web: www.cherrycorp.com