

ASSR-3210*, ASSR-3211*, ASSR-3220

General Purpose, Form A, Solid State Relay (250V/0.2A/10Ω)



Data Sheet

Description

The ASSR-32XX Series consists of an AlGaAs infrared light-emitting diode (LED) input stage optically coupled to a high-voltage output detector circuit. The detector consists of a high-speed photovoltaic diode array and driver circuitry to switch on/off two discrete high voltage MOSFETs. The relay turns on (contact closes) with a minimum input current of 3mA through the input LED. The relay turns off (contact opens) with an input voltage of 0.8V or less.

The single channel configurations, ASSR-3210 and ASSR-3211, are equivalent to 1 Form A Electromechanical Relays (EMR), and the dual channel configuration, ASSR-3220, is equivalent to 2 Form A EMR. They are available in 4-pin SO, 6-pin DIP, 8-pin DIP and Gull Wing Surface Mount for DIP packages. Their electrical and switching characteristics are specified over the temperature range of -40°C to +85°C. They are used for general purpose switching of signals and low power AC/DC loads.

ASSR-3211 enables AC/DC and DC-only output connections. For DC-only connection, the output current, I_{O} , increases to 0.4A and the on-resistance, $R(ON)$ reduces to 2.5Ω .

Applications

- Telecommunication Switching
- Data Communications
- Industrial Controls
- Medical
- Security
- EMR / Reed Relay Replacement

Features

- Compact Solid-State Bi-directional Signal Switch
- Single and Dual Channel Normally-off Single-Pole-Single-Throw (SPST) Relay
- 250V Output Withstand Voltage
- 0.2A or 0.4A Current Rating
(See Schematic for ASSR-3211 Connections A & B)
- Low Input Current:
CMOS Compatibility
- Low On-Resistance:
 2Ω Typical for DC-only, 8Ω Typical for AC/DC
- Very High Output Off-state Impedance:
10 Teraohms Typical
- High Speed Switching:
0.2ms (T_{on}), 0.02ms (T_{off}) Typical
- High Transient Immunity: $>1\text{kV}/\mu\text{s}$
- High Input-to-Output Insulation Voltage
(Safety and Regulatory Approvals Pending)
 - 3750 Vrms for 1 min per UL1577
 - CSA Component Acceptance

CAUTION: It is advised that normal static precautions be taken in handling and assembly of this component to prevent damage and/or degradation which may be induced by ESD.

* Advanced Information

Ordering Information

ASSR-3210-X03E

- 003E = Small Outline 4-Pin Package, 100 units per tube.
- 503E = Tape and Reel Packaging Option, 1500 units per reel.
- XXXE = Lead-Free Option.

ASSR-3211-X01E


- 001E = Standard DIP6 Package, 50 units per tube.
- 301E = Gullwing Packaging Option, 50 units per tube.
- 501E = Tape and Reel Packaging Option, 1000 units per reel.
- XXXE = Lead-Free Option.

ASSR-3220-X02E


- 002E = Standard DIP8 Package, 50 units per tube.
- 302E = Gullwing Packaging Option, 50 units per tube.
- 502E = Tape and Reel Packaging Option, 1000 units per reel.
- XXXE = Lead-Free Option.

Schematic


ASSR-3210




Equivalent
Relay
Diagram




ASSR-3211 Connection A



ASSR-3211 Connection B




ASSR-3220




Package Outline Drawings


ASSR-3210 4-Pin Small Outline Package



ASSR-3211 6-Pin DIP Package




ASSR-3211 6-Pin DIP Package with Gull Wing Surface Mount Option 300




NOTE: FLOATING LEAD PROTRUSION IS 0.25 mm (10 mils) MAX.

ASSR-3220 8-Pin DIP Package




DIMENSIONS IN MILLIMETERS AND (INCHES).
OPTION NUMBERS 300 AND 500 NOT MARKED.

ASSR-3220 8-Pin DIP Package with Gull Wing Surface Mount Option 300



NOTE: FLOATING LEAD PROTRUSION IS 0.25 mm (10 mils) MAX.

Lead Free IR Profile



NOTES:

THE TIME FROM 25°C TO PEAK TEMPERATURE = 8 MINUTES MAX.

$T_{smax} = 200^\circ\text{C}$, $T_{smin} = 150^\circ\text{C}$

Use of non-chlorine-activated fluxes is highly recommended.

Regulatory Information

The ASSR-3210, ASSR-3211 and ASSR-3220 are pending approval by the following organizations:

UL

Pending approval under UL 1577, component recognition program up to $V_{ISO} = 3750 V_{RMS}$

CSA

Pending approval under CSA Component Acceptance Notice #5.

Insulation and Safety Related Specifications

Parameter	Symbol	ASSR-3210	ASSR-3211, ASSR-3220	Units	Conditions
Minimum External Air Gap (Clearance)	L(101)	4.9	7.1	mm	Measured from input terminals to output terminals, shortest distance through air.
Minimum External Tracking (Creepage)	L(102)	4.9	7.4	mm	Measured from input terminals to output terminals, shortest distance path along body.
Minimum Internal Plastic Gap (Internal Clearance)		0.08	0.08	mm	Through insulation distance conductor to conductor, usually the straight line distance thickness between the emitter and detector.
Tracking Resistance (Comparative Tracking Index)	CTI	175	175	V	DIN IEC 112/VDE 0303 Part 1
Isolation Group (DIN VDE0109)		IIIa	IIIa		Material Group (DIN VDE 0109)

Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Units	Note
Storage Temperature	T _S	-55	125	°C	
Operating Temperature	T _A	-40	85	°C	
Junction Temperature	T _J		150	°C	
Lead Soldering Cycle	Temperature		260	°C	
	Time		10	s	
Input Current	Average	I _F	25	mA	
	Surge		50		
	Transient		1000		
Reversed Input Voltage	V _R		5	V	
Input Power Dissipation	ASSR-3220	P _{IN}	80	mW	
	ASSR-3211, ASSR-3210	P _{IN}	40	mW	
Output Power Dissipation	ASSR-3220	P _O	800	mW	
	ASSR-3211, ASSR-3210	P _O	400	mW	
Average Output Current (T _A = 25°C, T _C ≤ 100°C)		I _O	0.2	A	1
	ASSR-3211 Connection B	I _O	0.4	A	
Output Voltage (T _A = 25°C)		V _O	-250	250	V
	ASSR-3211 Connection B	V _O	0	250	V
Solder Reflow Temperature Profile		See Lead Free IR Profile			

Recommended Operating Conditions

Parameter	Symbol	Min.	Max.	Units	Note
Input Current (ON)	$I_F(ON)$	3	20	mA	2
Input Voltage (OFF)	$V_F(OFF)$	0	0.8	V	
Operating Temperature	T_A	-40	+85	°C	

Package Characteristics

Unless otherwise specified, $T_A = 25^\circ\text{C}$.

Parameter	Sym.	Min.	Typ.	Max.	Units	Conditions	Fig.	Note
Input-Output Momentary Withstand Voltage	V_{ISO}	3750			Vrms	$\text{RH} \leq 50\%$, $t = 1 \text{ min}$		3, 4
Input-Output Resistance	R_{I-O}		10^{12}		Ω	$V_{I-O} = 500 \text{ Vdc}$		
Input-Output Capacitance								
ASSR-3210	C_{I-O}		0.4		pF	$f = 1 \text{ MHz};$ $V_{I-O} = 0 \text{ Vdc}$	3	
ASSR-3211	C_{I-O}		0.5		pF			
ASSR-3220	C_{I-O}		0.8		pF			

Electrical Specifications (DC)

Over recommended operating $T_A = -40^\circ\text{C}$ to 85°C , $I_F = 5\text{mA}$ to 10mA , unless otherwise specified.

Parameter	Sym.	Min.	Typ.	Max.	Units	Conditions	Fig.	Note
Output Withstand Voltage	$ V_{O(OFF)} $	250	280		V	$V_F = 0.8\text{V}$, $I_O = 250 \mu\text{A}$, $T_A = 25^\circ\text{C}$		
		230			V	$V_F = 0.8\text{V}$, $I_O = 250 \mu\text{A}$	3	
Output Leakage Current	$I_{O(OFF)}$		0.03	100	nA	$V_F = 0.8\text{V}$, $V_O = 250\text{V}$, $T_A = 25^\circ\text{C}$		
			1		μA	$V_F = 0.8\text{V}$, $V_O = 250\text{V}$	4	
Output Offset Voltage	$ V_{(OS)} $		1		μV	$I_F = 5\text{mA}$, $I_O = 0\text{mA}$		
Input Reverse Breakdown Voltage	V_R	5			V	$I_R = 10 \mu\text{A}$		
Input Forward Voltage	V_F	1.1	1.3	1.7	V	$I_F = 5\text{mA}$	5, 6	
Output On-resistance	$R_{(ON)}$	8	10		Ω	$I_F = 5\text{mA}$, $I_O = 200\text{mA}$, Pulse $\leq 30\text{ms}$, $T_A = 25^\circ\text{C}$	7, 8	5
	ASSR-3211 Connection B	2.0	2.5		Ω			
	$R_{(ON)}$							

Switching Specifications (AC)

Over recommended operating $T_A = -40^\circ\text{C}$ to 85°C , $I_F = 5\text{mA}$ to 10mA , unless otherwise specified.

Parameter	Sym.	Min.	Typ.	Max.	Units	Conditions	Fig.	Note
Turn On Time	T_{ON}		0.25	1.0	ms	$I_F = 5\text{mA}$, $I_O = 200\text{mA}$, $T_A = 25^\circ\text{C}$	9, 13	
Turn Off Time	T_{OFF}		0.02	0.2	ms	$I_F = 5\text{mA}$, $I_O = 200\text{mA}$, $T_A = 25^\circ\text{C}$	11, 13	
Output Transient Rejection	dV_O/dt	1	7		kV/ μs	$\Delta V_O = 250\text{V}$, $T_A = 25^\circ\text{C}$	14	
Input-Output Transient Rejection	dV_{I-O}/dt	1	≥ 10		kV/ μs	$\Delta V_{I-O} = 1000\text{V}$, $T_A = 25^\circ\text{C}$	15	

Notes:

- For derating, refer to Figure 1 and 2.
- Threshold to switch device is $I_F \geq 0.5\text{mA}$, however, for qualified device performance over temperature range, it is recommended to operate at $I_F = 5\text{mA}$. Refer to application information in next section of this datasheet.
- Device is considered as a two terminal device: pins 1, 2, 3 and 4 shorted together and pins 5, 6, 7 and 8 shorted together.
- The Input-Output Momentary Withstand Voltage is a dielectric voltage rating that should not be interpreted as an input-output continuous voltage rating. For the continuous voltage rating refer to the IEC/EN/DIN EN 60747-5-2 Insulation Characteristics Table (if applicable), your equipment level safety specification, or Avago Technologies Application Note 1074, "Optocoupler Input-Output Endurance Voltage."
- During the pulsed $R_{(ON)}$ measurement (I_O duration $\leq 30\text{ms}$), ambient (T_A) and case temperature (T_C) are equal.




Figure 1. Maximum Average Output Current Rating vs Ambient Temperature




Figure 2. Output Power Derating vs Case Temperature




Figure 3. Normalized Typical Output Withstand Voltage vs. Temperature




Figure 4. Typical Output Leakage Current vs. Temperature




Figure 5. Typical Forward Voltage vs. Temperature




Figure 6. Typical Forward Current vs. Forward Voltage




Figure 7. Typical On Resistance vs. Temperature




Figure 8. Typical Output Current vs. Output Voltage




Figure 9. Typical Turn On Time vs. Input Current




Figure 10. Typical Turn On Time vs. Temperature




Figure 11. Typical Turn Off Time vs. Input Current




Figure 12. Typical Turn Off Time vs. Temperature







Figure. 13 Switching Test Circuit for TON, TOFF



$$\frac{dV_o}{dt} = \frac{(0.8)V_{PEAK}}{t_R} \text{ OR } \frac{(0.8)V_{PEAK}}{t_F}$$

OVER SHOOT ON V_{PEAK} IS TO BE 10%

Figure. 14. Output Transient Rejection Test Circuit




Figure 15. Input-Output Transient Rejection Test Circuit

Applications Information

On-Resistance and Derating Curves

The Output On-Resistance, $R_{(ON)}$, specified in this data sheet, is the resistance measured across the output contact when a pulsed current signal ($I_o=200mA$) is applied to the output pins. The use of a pulsed signal ($\leq 30ms$) implies that each junction temperature is equal to the ambient and case temperatures. The steady-state resistance, R_{ss} , on the other hand, is the value of the resistance measured across the output contact when a DC current signal is applied to the output pins for a duration sufficient to reach thermal equilibrium. R_{ss} includes the effects of the temperature rise in the device.

Derating curves are shown in Figures 1 and 2. Figure 1 specifies the maximum average output current allowable for a given ambient temperature. Figure 2 specifies the output power dissipation allowable for a given case temperature. Above a case temperature $102^{\circ}C$, the maximum allowable output current and power dissipation are related by the expression $R_{ss}=Po(max)/(I_o(max))^2$ from which R_{ss} can be calculated. Staying within the safe area assures that the steady state MOSFET junction temperature remains less than $150^{\circ}C$.

Turn On Time and Turn Off Time Variation

The ASSR-32xx Series exhibits a very fast turn on and turn off time. Both the turn on and turn off time can be adjusted by choosing proper forward current as depicted in Figures 9 and 11. The changes of the turn on and turn off time with ambient temperature are also shown in Figures 10 and 12.

For product information and a complete list of distributors, please go to our web site: www.avagotech.com

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies, Pte. in the United States and other countries.
Data subject to change. Copyright © 2006 Avago Technologies Pte. All rights reserved. Obsoletes AV01-0114EN
AV01-0359EN - August 10, 2006

