

SKINDICHT®

Accessories and separate gland parts
Blanking plugs of polystyrene and polyamide
with PG thread

SKINDICHT® BLK / BLK-GL Blanking plugs

made of polystyrene or glass-
fibre reinforced polyamide are
used wherever threads pre-
viously cut must be closed.



Technical Data



Material:
BLK: Polystyrene
BLK-GL: Polyamide reinforced
with glass fibre



Colour: RAL 7035 light grey



Temperature range:
BLK: -20 °C to +70 °C
BLK-GL: -40 °C to +100 °C

Part number	Type PG size	Thread length mm	Pack size pieces
SKINDICHT® BLK			
5200 5949	BLK 7	6	100
5200 5950	BLK 9	6	100
5200 5960	BLK 11	6	100
5200 5970	BLK 13,5	6	100
5200 5980	BLK 16	6	100
5200 5990	BLK 21	8	50
5200 6000	BLK 29	8	50
5200 6010	BLK 36	10	25
5200 6020	BLK 42	10	25
5200 6030	BLK 48	12	25

SKINDICHT® BLK-GL

5202 4848	BLK-GL 7	6	100
5202 4849	BLK-GL 9	6	100
5202 4850	BLK-GL 11	6	100
5202 4851	BLK-GL 13,5	6	100
5202 4852	BLK-GL 16	6	100
5202 4853	BLK-GL 21	8	50
5202 4854	BLK-GL 29	8	50
5202 4855	BLK-GL 36	10	25
5202 4856	BLK-GL 42	10	25