COMPONENTS, CONNECTORS & CABLING GUID		
	5000	
	B	
Please check out www.deltron-emcon.com for full technical specifications		

Ш

Series: Insulated S Part Number Selection With Cable Clamp	Speaker Line Nickel 658-0000	Socket			
Series: Phono Cor Part Number Selection Black Red	nnector Econ Nickel 425-0100 425-0500	omy			
Series: Standard I Part Number Selection Black (Nickel) Red (Nickel) Black (Gold) Red (Gold)	•	ulated Housin Solid Pin 415-0100 415-0500 416-0100 416-0500	g		
Series: Standard S Part Number Selection Black Red	Socket with I Nickel 433-0100 433-0500	nsulated Hous	sing		
AUDIO / MUS Deltron Emcon offer Gotham Audio Cables on the conductors, re Deltron Emcon have a volume bespoke cable	both audio cables. Featuring the sults in superb taccess to the co	e, and audio cable unique 'Double I flexibility and the	assemblies using p Reussen Shielding best possible RF re	professional cable which is two layer ejection up to 130	provided by s of copper wire dB.
4MM SINGL A range of 4mm prod range caters for a bro plated unless otherwis Series: Standard I > Solder Bucket Term > Stainless Steel Com Part Number Selection Black Blue Brown	ucts offering ma ad range of inst se stated. Plug iination	any unique feature	es and manufacture	d to a very high s is. All contact ma tal moulding	tandard. This
Series: Standard I Large Solder Bucke Supplied with Insula Cable up to 7.1mm Rated at 10 Amps Part Number Selection Black Blue Brown Green	t Connection ating Cover to A	-	 Accepts Cond Stainless Stee 	n ductors up to 5.5n l Contact Spring I old Plating for Red Nickel Plated 579-0500 579-0500 579-0700	ncorporated

	Plugs with order code Part Number Selection Black Red	es 583 and 584 fer Nickel Plated 583-0100 583-0500	ature solder, scre Black Plated 584-0100 584-0500	ew or crimp termination.
	Series: Triple Con Screw Connection Accepts Cables to Rated at 10 Amps Part Number Selection Black Blue Brown Green	for the Lead Wire	Red White Yellow	 Screw-on Rigid Acetal Moulding Accepts Conductor to 3.5mm Diameter 557-0500 557-0600 557-0700
	Series: Stackable > Screw Connection > Rated at 10 Amps Part Number Selection Black Blue Brown Green	-	e Red White Yellow	 Push-on Pliable PVC Moulding 553-0500 553-0600 553-0700
Contraction of the second s	Series: Bunch Pin Screw Connection Rated at 20 Amps Part Number Selection Black Blue Brown Green		0	 Push-on Pliable PVC Moulding 555-0500 555-0600 555-0700
	Series: 4mm Aud High Quality Audio Connection is mad Designed primarily for Terminating He Inter-Connection b Part Number Selection Black Red	o Plug le by a Knurled Sc for use in the Au avy-Duty Speaker	dio Industry Cable, and	 Cross Hole to Accept Cable to 7.5mm Diameter and 4mm Plug in the Clamp Screw Supplied in Gold Plated Finish
A Real Provide A Real	Series: Rear Spea Large Cable Entry up to 7.5mm Diam Speaker Connectio a 4mm hole in the through the cross Part Number Selection Black Red	Hole which Accep neter on can be Terminat clamp screw, or c	ed by either lamped	 Ideally Suited for Rear Termination of Speakers Gold Plated Finish

Please check out www.deltron-emcon.com for full technical specifications



