

Features:

- * European AC Input 200—240Vac
- * Low ripple & noise
- * No minimum load requirement
- * 100% test
- * 1 year warranty
- * Safety: TUV, CE



SPECIFICATION:

MODEL NO.	DSA-0151A-05	DSA-0151A-06	DSA-0151A-07	DSA-0151A-09	DSA-0151A-12	DSA-0151A-15	
PART NO.	S2200ST	S2104ST	S2105ST	SS2106ST	S2107ST	S2108ST	
OUTPUT:							
Voltage	5V	6V	7.5V	9V	12V	15V	
Current (Max)	2.4A	2.0A	1.8A	1.5A	1.25A	1.0A	
Current (Min)	0A						
Line Regulation	+/-2%						
Total Regulation	+/-5%						
Over Voltage Protection	8.0Vdc Max	9.6Vdc Max	13.5Vdc Max	15.0Vdc Max	19.5Vdc Max	23.4Vdc Max	
Over Current Protection	4.8A Max With Auto Recovery	4.0A Max With Auto Recovery	3.6A Max With Auto Recovery	3.0A Max With Auto Recovery	2.5A Max With Auto Recovery	2.0A Max With Auto Recovery	
Ripple Voltage (L-F)	120mV p-p	120mV p-p	120mV p-p	120mV p-p	120mV p-p	150mV p-p	
O/P Connector (1.8M Jack Lead)	Multichoice 7 Pack						
SAFETY:							
Hi Pot Test I/P-O/P	3KVac or 4242Vdc						
Insulation I/P-O/P	Not Specified						
TEMPERATURE:							
Operating	0 to 40°C						
Storage	-20 to 60°C						
HUMIDITY:							
Operating	20 to 80% Non Condensing						
Storage	5 to 90% Non Condensing						
INPUT:							
Voltage	200-240Vac						
Frequency	50-60Hz						
Current RMS (Max)	400mA						
Inrush Current	Not Specified						
Leakage Current	0.25A						
Efficiency (Min)	65%						
MTBF	50K Hours						
Safety	EN 60950-1						
Additional Safety							
EMI	EN 55022						
EMC	EN 5082-1, EN 61000-3-2, EN 61000-3-3						

1 ARKWRIGHT ROAD, READING, BERKS. RG2 0LU

TEL: 0118 9311199

FAX: 0118 9311145

E-Mail: info@stontronics.co.uk www.stontronics.co.uk

DSA-0151A-XX 15W SERIES

Dimensions:

Weight: 190g Approx.

