

A complete range of miniature monochrome cameras offering a variety of lens and mounting options.

◆ CEC C38

Measuring only 62mm long and 42mm wide, this camera is made from injection moulded plastic with a tinted viewing window and comes complete with an integral bracket. The unit is easy to install, with power connection via the rear terminal strip. The integral 3.8mm lens can be adjusted and then locked into position, giving a 60° angle of view.

◆ MD60 & MD38

The complete unit is housed in a dome and base unit, both are made from injection moulded plastic, the base is finished in white while the dome has a frosted finish. The camera is very compact and discreet making it ideal for retail or public areas. The head can be moved in 2 planes allowing wall or ceiling mounting. 2 lens options are available, 3.8mm and 6.0mm, both giving excellent picture quality at a very low price.

◆ MCH60 & MCH38

This is a fully weather proof external camera with mounting bracket. Available with 3.8 or 6mm lenses and finished in black. This unit is ideal for sensitive areas where appearance is important. Installation is very simple, the camera is prewired with a length of cable and only needs to be connected to a 12vDC supply and video cable. The IP65 housing is constructed from aluminium and measures 70mm long by 38mm square.

SPECIFICATION			
	CEC C38	MD38 & MCH38	MD60 & MCH60
IMAGE SENSOR EFFECTIVE PIXELS RESOLUTION SENSITIVITY S/N RATIO SYNCHRONISATION POWER VOLTAGE POWER CURRENT CONNECTION LENS	1/3" INTERLINE CCD 512(H) x 582(V) > 380 TV LINES < 0.6 LUX > 47dB INTERNAL 9vDC < 200mA 2 WAY TERMINAL STRIP 3.8mm F2.0	1/3" INTERLINE CCD 512(H) x 582(V) > 380 TV LINES < 0.6 LUX > 47dB INTERNAL 12VDC < 200mA 4 WAY TERMINAL STRIP 3.8mm F2.0	1/3" INTERLINE CCD 512(H) x 582(V) > 380 TV LINES < 0.9 LUX > 47dB INTERNAL 12VDC < 200mA 4 WAY TERMINAL STRIP 6.0mm F2.5

comput Computar House 6 Garrick Industrial Centre, Garrick Road, London NW9 6AQ

Tel: 0181 732 3334/3324/3310 Fax: 0181 202 3387