

# 16-2-xxA & 16-2-xxC Series

## Defence Standard 61-12 Part 5

**PRO-POWER**  
Quality Cables



### Applications

These cables are suitable as interconnections between and within instruments and electrical equipment for such applications as data transmission and process control.

### Technical Data

Maximum conductor temperature	: +70°C.
Minimum ambient temperature	: -55°C after installation and only when cable is in a fixed position.
Current rating	: Maximum of 2.5A per core.
Maximum working voltage (U <sub>o</sub> /U)	: (U <sub>o</sub> /U) 440V r.m.s at frequencies up to 1600Hz.
Test voltage	: 2KV r.m.s. between conductors and between conductors and screen, where applicable.
Maximum conductor resistance	: 40.1Ω/Km at 20°C.
Minimum insulation resistance	: 11MΩ/Km at 20°C.
Conductor area	: 0.5mm <sup>2</sup> per core.
Spread of flame	: BS EN 50265-2-1 : Part 1, HD 405-1, IEC 332-1

### DEF STAN 61-12 Part 5

#### Type A Unshielded

##### Construction

- 16/0.2mm (0.5mm<sup>2</sup>) tinned annealed copper conductor.
- Type 16-2-A PVC sheathed overall to BS 6746 having the colours listed in the 'Identification' table.
- PVC insulated, Polyester binder tape.

### DEF STAN 61-12 Part 5

#### Type C Screened

##### Construction

- 16/0.2mm(0.5mm<sup>2</sup>) tinned annealed copper conductors.
- Type 16-2-C PVC sheathed overall to BS 6746 having the colours listed in the 'Identification' table.
- PVC insulated, Polyester binder tape, tinned copper braid screened overall.

### DEF STAN 61-12 Part 5 - Screened

#### Specifications:

Conductors	: 16/0.2mm.
Voltage Rating	: 440V (RMS).
Conductor Area	: 0.5mm <sup>2</sup> per core.
Sheath Colour	: Black.
Maximum Current per core	: 2.5A.
Maximum Operating Temperature	: 70°C

# 16-2-xxA & 16-2-xxC Series

## Defence Standard 61-12 Part 5

### PHYSICAL DATA

Cable Reference	Number of Cores	Nominal Diameter	Reel Length (m)	Type	Part Number
16-2-1C	1	3.8	100	Screened	860038 100M
16-2-2C	2	6.9	25		860008
			100		860008 100M
16-2-3C	3	7.2	25		860155 25M
			100		860155 100M
16-2-4C	4	7.7	25		860009
			100		860009 100M
16-2-6C	6	8.7	25		860010
			100		860010 100M
16-2-8C	8	9.2	25		860011 25M
			100		860011 100M
16-2-12C	12	11.0	25		860012 25M
			100		860012 100M
16-2-18C	18	12.5	25		MCCP-1620T-N18C-AXX-61
			100		MCCP-1620T-N18C-AXX-64
16-2-25C	25	14.6	25		MCCP-1620T-N25C-AXX-61
			100		7001551
16-2-2A	2	5.9	25		850009
			100		850009 100M
16-2-3A	3	6.2	25		850038
			100	850038 :	
16-2-4A	4	6.7	25	850010	
			100	850010 100M	
16-2-6A	6	7.7	25	850011	
			100	850011 100M	
16-2-8A	8	8.5	25	850077 25M	
			100	850077	
16-2-12A	12	9.9	25	850013	
			100	850013 100M	
16-2-18A	18	11.5	25	850014	
			100	7001562	
16-2-25A	25	13.6	25	850015	
			100	850015 100M	

Dimensions : Millimetres (Unless Specified)

# 16-2-xxA & 16-2-xxC Series

## Defence Standard 61-12 Part 5

### IDENTIFICATION

Number of Cores	Colour
1	Red
2	Blue
3	Green
4	Yellow
6	Black
7	Brown
8	Violet
9	Orange
10	Pink
11	Turquoise
12	Grey
13	RED/Blue
14	GREEN/Red
15	YELLOW/Red
16	WHITE/Red
17	RED/Black
18	RED/Brown
19	YELLOW/Blue
20	WHITE/Blue
21	BLUE/Black
22	ORANGE/Blue
23	GREEN/Blue
24	GREY/Blue
25	YELLOW/Green
26	WHITE/Green
27	GREEN/Black
28	ORANGE/Green
29	GREY/Green
30	YELLOW/Brown
31	WHITE/Brown
32	BROWN/Black
33	GREY/Brown
34	YELLOW/Violet
35	VIOLET/Black
36	WHITE/Violet

**Note:** For bi-coloured cores the base colour is shown in capitals. Cables with more than 36 cores have a Red and a Blue core laid adjacent to one another in each layer, the remainder of the cores being White.

# 16-2-xxA & 16-2-xxC Series

## Defence Standard 61-12 Part 5

**PRO-POWER**  
Quality Cables

### Notes:

### International Sales Offices:



**AUSTRALIA – Farnell InOne**  
Tel No: ++ 61 2 9645 8888  
Fax No: ++ 61 2 9644 7898



**FINLAND – Farnell InOne**  
Tel No: ++ 358 9 560 7780  
Fax No: ++ 358 9 345 5411



**NETHERLANDS – Farnell InOne**  
Tel No: ++ 31 30 241 7373  
Fax No: ++ 31 30 241 7333



**SWITZERLAND – Farnell InOne**  
Tel No: ++ 41 1 204 64 64  
Fax No: ++ 41 1 204 64 54



**AUSTRIA – Farnell InOne**  
Tel No: ++ 43 662 2180 680  
Fax No: ++ 43 662 2180 670



**FRANCE – Farnell InOne**  
Tel No: ++ 33 474 68 99 99  
Fax No: ++ 33 474 68 99 90



**NEW ZEALAND – Farnell InOne**  
Tel No: ++ 64 9 357 0646  
Fax No: ++ 64 9 357 0656



**UK – Farnell InOne**  
Tel No: ++ 44 8701 200 200  
Fax No: ++ 44 8701 200 201



**BELGIUM – Farnell InOne**  
Tel No: ++ 32 3 475 2810  
Fax No: ++ 32 3 227 3648



**GERMANY – Farnell InOne**  
Tel No: ++ 49 89 61 39 39 39  
Fax No: ++ 49 89 613 59 01



**NORWAY – Farnell InOne**  
Tel No: ++ 45 44 53 66 66  
Fax No: ++ 45 44 53 66 02



**UK – BuckHickman InOne**  
++ 44 8450 510 150  
++ 44 8450 510 130



**BRAZIL – Farnell-Newark InOne**  
Tel No: ++ 55 11 4066 9400  
Fax No: ++ 55 11 4066 9410



**HONG KONG – Farnell-Newark InOne**  
Tel No: ++ 852 2268 9888  
Fax No: ++ 852 2268 9899



**PORTUGAL – Farnell InOne**  
Tel No: ++ 34 93 475 8804  
Fax No: ++ 34 93 474 5288



**UK – CPC**  
++ 44 8701 202 530  
++ 44 8701 202 531



**CHINA – Farnell-Newark InOne**  
Tel No: ++86 10 6238 5152  
Fax No: ++86 10 6238 5022



**IRELAND – Farnell InOne**  
Tel No: ++ 353 1 830 9277  
Fax No: ++ 353 1 830 9016



**SINGAPORE – Farnell-Newark InOne**  
Tel No: ++ 65 6788 0200  
Fax No: ++ 65 6788 0300



**EXPORT – Farnell InOne**  
Tel No: ++ 44 8701 200 208  
Fax No: ++ 44 8701 200 209

For enquiries from all other markets



**DENMARK – Farnell InOne**  
Tel No: ++ 45 44 53 66 44  
Fax No: ++ 45 44 53 66 06



**ITALY – Farnell InOne**  
Tel No: ++ 39 02 93 995 200  
Fax No: ++ 39 02 93 995 300



**SPAIN – Farnell InOne**  
Tel No: ++ 34 93 475 8805  
Fax No: ++ 34 93 474 5107



**ESTONIA – Farnell InOne**  
Tel No: ++ 358 9 560 7780  
Fax No: ++ 358 9 345 5411



**MALAYSIA – Farnell-Newark InOne**  
Tel No: ++ 60 3 7873 8000  
Fax No: ++ 60 3 7873 7000



**SWEDEN – Farnell InOne**  
Tel No: ++ 46 8 730 50 00  
Fax No: ++ 46 8 83 52 62

<http://www.farnellinone.com>

<http://www.buckhickmaninone.com>

<http://www.cpc.co.uk>

**Disclaimer** This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-Power is the registered trademark of the Group. © Premier Farnell plc 2004.