



[HOME](#) || [DISTRIBUTORS](#) || [ABOUT US](#)

[SEARCH](#)
Advanced

DMMs : Triple Display PC Interface DMM

Model No. 72-6780



Features:

- 3 3/4 digit, 4000 count LCD display with two sub-displays and bargraph
- Main and secondary function menus
- Autoranging
- AC/DC voltage and current
- Resistance
- Capacitance
- Frequency counter
- Transistor gain
- Diode test
- Continuity beeper
- RS-232 communication
- Data hold
- Record/recall function
- MIN/MAX/AVG
- Relative mode
- Time stamp
- Meets IEC1010 safety standards for 600V CAT III and 1000V CAT II applications
- Includes test leads with alligator clips, holster, 9V battery and owners manual

Analyzers

Spectrum Analyzers

Audio

Audio Generators

Dummy Loads

Sound Level Meters

Cable Testers

Break Out Boxes

PC Cable

Counters

Frequency

Handheld Frequency

Universal

Engine Analyzers

Engine Analyzers

Hand Tools

SMD Tweezers

Meters

AC Clamp On

AC Millivolt

Anemometers

Capacitance

Clamp Adaptors

Current Loop

Calibrators

DMMs

ESR Meters

Holsters

LCR

Light

Mini AC Clamp

Moisture

Pen DMM

Photo Tachometers

Temperature

Thermo Anemometers

VOMs

Oscilloscopes

Cases

Handheld

Oscilloscope Cases

Probes

Scopes

Spectrum Analyzer

Adapters

Power

DC Power Supplies

High Current

Isolated AC

Isolation Transformers

Lab Power Supplies

Line Splitters

Variacs

Specifications	Range	Max Resolution	Basic Accuracy
DC voltage	400mV, 4V, 40V, 400V, 1000V	0.1mV	(0.5% + 5 digits)
AC voltage	400mV, 4V, 40V, 400V, 700V	0.1mV	1.0% + 10 digits
DC current	400mA, 20A	100°A	±(1.2% + 5 digits)
AC current	400mA, 20A	100µA	1.5% + 10 digits
Resistance	400ohms, 4Kohms, 40Kohms, 400Kohms, 4Mohms, 40Mohms	0.1ohms	±(0.75% + 5 digits)
Capacitance	4nF, 40nF, 400nF, 4µF, 40µF	1pF	±3% + 10 digits)
Frequency	4KHz, 40KHz, 400KHz, 4MHz	1Hz	±(0.1% + 10 digits)
Dimensions/weight	3 5/8" (W) x 1 1/2" (H) x 7 1/2" (L)/1 lb.		