



PANEL MOUNTING

SOLDER LUG

SPECIFICATIONS
ELECTRICAL LIFE: 40,000 make-and-break cycles at full load.
CONTACT RESISTANCE: 10m Ω max. initial @ 2-4VDC
 100mA for both silver and gold plated contacts.
INSULATION RESISTANCE: 1,000M Ω min.
DIELECTRIC STRENGTH: 1,000 V RMS@sea level.
OPERATING TEMPERATURE: -30° C to 85° C.

MATERIALS
CASE: Dially phthalate (DAP) (UL94V-0).
ACTUATOR: Brass, chrome plated.
BUSHING: Brass, nickel plated.
HOUSING: Stainless Steel.
TERMINAL/CONTACT: Silver or gold plated.

RATING:

R : 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)
 Q : 2Amps @250VAC
 5Amps @120 VAC or 28 VDC

Model No.	POS.1	POS.2	POS.3
	ON	NONE	ON
1M31 Term. Comm.	2-3,5-6,8-9	NONE	2-1,5-4,8-7
SCHEMATIC			

SWITCH FUNCTION

符號	原尺寸	修改後尺寸	變更日期
1	(A)		
2	(B)		
3	(C)		
4	(D)		
5	(E)		

SCALE (比例): 3 : 2

TOLERANCE (公差):
 0.00 mm ± 0.25mm
 0.0 mm ± 0.40mm
 ANGULAR: ± 2.54 mm

FILE NAME: 1M3P0001

德利威電子股份有限公司
DAILYWELL ELECTRONICS CO.,LTD.

TITLE 圖名	Miniature Toggle Switches			SIZE 圖紙	A4
DWG NO. 圖號	1M31T1B1M1QE			UNIT 單位	inch
REV. 版本	A	DATA 日期	MAR - 29 - 2002	SHEET 張數	1 of 1
CHECKED BY 審核	JACK		DRAWN BY 製圖	BOBO	