


Open Grommets

PRO-POWER
Quality Cables



Specifications:

Maximum constant working temperature : 70°C.
 Minimum constant temperature : -35°C.
 Black PVC normal shore hardness : 43°C to 55°C.



Dimensions : Millimetres

Specification Table

A	B	C	D	E	Part Number
4.8	1.6	3.2	6.4	8.0	PV2 GROMMET PK 100
6.4	1.2	4.0	4.0	9.5	PV710 GROMMET PK 100
	1.6		6.4		PV5 GROMMET PK 100
7.1		PV6 GROMMET PK 100			
8.0		4.8	6.4	11.1	PV24 GROMMET PK 100
9.5		6.4	5.6	12.7	PV35 GROMMET PK 100
			4.8		PV36A GROMMET PK 100
			6.4	14.3	PV36 GROMMET PK 100
			7.5	13.5	PV45 GROMMET PK 100
10.3		8.0	4.8	14.3	PV37A GROMMET PK 100
11.1		7.2	6.4	15.9	PV44 GROMMET PK 100
			8.0		PV837 GROMMET PK 100
11.9	8.0	4.8	14.3	PV50A GROMMET PK 100	
	6.4	8.0	15.9	PV231 GROMMET PK 100	
12.7	9.5	6.8	17.5	PV233 GROMMET PK 100	
		6.3	15.9	PV53 GROMMET PK 100	
14.3	11.1	6.4	19.0	PV64 GROMMET PK 100	
19.0	12.7		25.4	PV73A GROMMET PK 100	
20.0	15.9		23.8	PV73M GROMMET PK 100	
25.4	19.0	7.5	30.0	PV93 GROMMET PK 100	

Dimensions : Millimetres

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-Power is the registered trademark of the Group. © Premier Farnell plc 2009.

<http://www.farnell.com>
<http://www.newark.com>
<http://www.cpc.co.uk>

PRO-POWER
Quality Cables