



CXXX
 WEEK NO. FOR YEAR.
 YEAR NO.
 "C" FOR MOLEX CHINA
DETAIL C

88741-8121	DVI_D-DVI_D DUAL LINK CABLE 5M PARCHMENT WHT	5000 ± 150 196.9 ± 5.9	PARCHMENT WHITE	887808369
88741-8111	DVI_D-DVI_D DUAL LINK CABLE 3M PARCHMENT WHT	3000 ± 80 118.1 ± 3.1	PARCHMENT WHITE	887808369
88741-8101	DVI_D-DVI_D DUAL LINK CABLE 2M PARCHMENT WHT	2000 ± 60 78.7 ± 2.4	PARCHMENT WHITE	887808369
88741-8120	DVI_D-DVI_D DUAL LINK CABLE 5M BLK	5000 ± 150 196.9 ± 5.9	BLACK	887808368
88741-8110	DVI_D-DVI_D DUAL LINK CABLE 3M BLK	3000 ± 80 118.1 ± 3.1	BLACK	887808368
88741-8100	DVI_D-DVI_D DUAL LINK CABLE 2M BLK	2000 ± 60 78.7 ± 2.4	BLACK	887808368
MX P/N	DESCRIPTION	LENGTH	CABLE COLOR	CABLE P/N

ENTER DESCRIPTION EC NO: DG2006-0159 DRWN: PDAI CHKD: APPR: TKAN	2006/01/16 2006/01/16 2006/01/18	QUALITY SYMBOLS ▽=0 ◻=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
					MM/IN	---	METRIC		
			4 PLACES	± ---	± ---	DRAWN BY	DATE	TITLE	
			3 PLACES	± ---	± ---	PDAI	2006/01/11	DVI_D DUAL LINK CABLE	
			2 PLACES	± ---	± ---	CHECKED BY	DATE		
			1 PLACE	± ---	± ---	ZXDENG	2006/01/11		
			ANGULAR ± ---°		APPROVED BY	DATE	MOLEX MOLEX INCORPORATED		
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		BORON	2006/01/11	MOLEX MOLEX INCORPORATED		
					MATERIAL NO.	DOCUMENT NO.	SHEET NO.		
					SEE TABLE	SD-88741-002	1 OF 2		
					SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
					A 4				

7 6 5 4 3 2 1

E

E

8. CONNECTION DIAGRAM

SHIELD	SHIELD	GROUND
PIN 24	PIN 24	TMDS CLOCK-
PIN 23	PIN 23	TMDS CLOCK+
PIN 22	PIN 22	TMDS CLOCK SHIELD
PIN 21	PIN 21	TMDS DATA 5+
PIN 20	PIN 20	TMDS DATA 5-
PIN 19	PIN 19	TMDS DATA 0/5 SHIELD
PIN 18	PIN 18	TMDS DATA 0+
PIN 17	PIN 17	TMDS DATA 0-
PIN 16	PIN 16	HOT PLUG DETECT
PIN 15	PIN 15	GROUND(+5V)
PIN 14	PIN 14	POWER +5V
PIN 13	PIN 13	TMDS DATA 3+
PIN 12	PIN 12	TMDS DATA 3-
PIN 11	PIN 11	TMDS DATA 1/3 SHIELD
PIN 10	PIN 10	TMDS DATA 1+
PIN 9	PIN 9	TMDS DATA 1-
PIN 7	PIN 7	DDC DATA
PIN 6	PIN 6	DDC CLOCK
PIN 5	PIN 5	TMDS DATA 4+
PIN 4	PIN 4	TMDS DATA 4-
PIN 3	PIN 3	TMDS DATA 2 /4 SHIELD
PIN 2	PIN 2	TMDS DATA 2+
PIN 1	PIN 1	TMDS DATA 2-
DVI_D	DVI_D	CABLE FUNCTION

NOTE:1. OVERMOLD SPECIFICATION
 1.1 DVI BOOT MOLDED WITH SNOW WHITE PVC RESIN P/N IS 887800076.
 1.2 UL94V-0, COLOR: MAD432
 1.3 HARDNESS (DUROMETER): SHORE A 90-95
 2. MECHANICAL SPECIFICATION
 2.1 CABLE SHOULD STAND THE PULL FORCE 89-111N FOR 30 SECONDS WITH NO VISIBLE TERMINATION DAMAGE.
 2.2 CABLE SHOULD PASS THE FLEX TEST IN 100 CYCLES AT EACH OF PLANES, PER EIA 364-41, CONDITION I.
 3. CABLE ELECTRICAL SPECIFICATION
 3.1 DIELECTRIC STRENGTH: 500VDC FOR 10mS.
 3.2 INSULATION RESISTANCE: 50 MEGA Ohms
 3.3 DIFFERENTIAL LINES CHARACTERISTIC IMPEDANCE: 100 ± 7 Ohms @TDR.
 4. DVI CONNECTOR SPECIFICATION
 4.1 REFER TO PRODUCT SPEC. PS74320-0001.
 4.2 CONTACT PLATING: AU FLASH.
 5. SHORTCIRCUIT AMONG DRAIN WIRES SIGNAL GROUND IS ACCEPTABLE IN DVI CABLE.
 6. THIS PRODUCT MUST MEET MX RoHS COMPLIANCE.

D

D

C

C

7. MATERIAL LIST

C	DVI THUMB SCREW 887806077
B	DVI_D DUAL CHANNEL G/F CONNECTOR 743230003
A	DVI DULA LINK CABLE (SEE TABLE)
ITEM	DESCRIPTION

B

B

A

A

ENTER DESCRIPTION EC NO: DG2006-0159 DRWN: PDAI 2006/01/16 CHKD: 2006/01/16 APPR: TKAN 2006/01/18	QUALITY SYMBOLS 	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
				MM/IN		---	METRIC		
				mm	INCH	DRAWN BY	DATE		TITLE
						PDAI	2006/01/11		DVI_D DUAL LINK CABLE
		4 PLACES	± ---	± ---	CHECKED BY	DATE			
		3 PLACES	± ---	± ---	ZXDENG	2006/01/11			
		2 PLACES	± ---	± ---	APPROVED BY	DATE			
		1 PLACE	± ---	± ---	BORON	2006/01/11			
		ANGULAR ± ---°		MATERIAL NO.		DOCUMENT NO.		SHEET NO.	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE		SD-88741-002		2 OF 2	
				SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
				A 4					

6 5 4 3 2 1