


仕様
SPECIFICATION

耐電圧 : AC500V 1分間
 DIELECTRIC STRENGTH:500V AC FOR ONE MINUTE.
 接触抵抗 : 50mΩ以下
 CONTACT RESISTANCE:50mΩ MAX
 絶縁抵抗 : DC100Vにて100MΩ以上
 INSULATION RESISTANCE:100MΩ MIN.AT 500V DC.

回路図
CIRCUIT



LET	PART NAME	MATERIAL	QTY	FINISH	NOTE	TOLERANCE	SCALE	DATE	DESIG	DRAW	INSPE	APRO
7	CAP	PE	1				4/1	14/12/15		M,K		
6	CONTACT D	BSR t=0.3	1	Ni		MODEL		QTY	PART NAME	4-CONDUCTOR SUB-MINIATURE IN-LINE JACK		
5	CONTACT C	FAB-EH t=0.3	1	Ni		型式			品名	No.MJ068		
4	CONTACT B	FAB-EH t=0.3	1	Au		MATERIAL				DRAW.NO	MJ068	
3	CONTACT A	FAB-EH t=0.25	1	Ni		材質				図番		
2	SLEEVE	BSR	1	Ni		FINISH						
1	BODY	PA	1			処理						

EST MARUSHIN ELECTRIC MFG.CO.,LTD.