| CONVERTED FROM PS0441 ISS6 (16.02.96) IN JAN 2003 DrgNo 730-731 TITLE PROFESSIONAL QUALITY MICRC DELTRON Components S S GENERAL SPECIFICATION CUSTOMER FOR 730-731 Aprvd Date © Deltron Emcon Limited E-Mail components@deltron-emcon.com, Website www.deltron-emcon.com. Photometry Photometry | Dimensions | A range of leads featuring high quality, low noise Gotham microphone cable. The double lap screened cable is ideally suited to studio applications due to its construction, each lap screen being wound in opposite directions. This feature provides unsurpassed noise rejection yet still maintains a high degree of flexibility. |
|---|--|--|
| MICROPHONE LEADS STOMER rvd Date 16.02.96 Aprvd By m. Phone +44 1724 273200 | NICKEL 730-0010 730-0030 730-0050 730-0100 | |
| FILTER MC Drwn b Fax +44 172 | BLACK 731-0010 731-0030 731-0050 731-0100 | 3 w Prc 3 w Prc Prc |
| ALL DIMENSIONS IN MM ANGLES IN DECIMAL DEGREES REF y BFS Scale: NTS Sheet 1 / 1 14 270230 | LENGTH 1.0m 5.0m 10.0m | 3 way Free Plug as per Product Specification 701-709-705-713 3 way Free Socket as per Product Specification 700-708-704-712 Cable GAC-2 as per Product Specification 439 Series |