

Scotchcast BK Series In-line Joint

In Line Joint for PVC/PVC/SWA/PVC & XLPE Insulated Cables 0.6/1kv Designed for Street Lighting Applications

Kit includes two-part mould, polyetherurethane Resin No. 47, armour continuity, tape, and full instructions

Use combination of conductor size / number of cores to select Kit type.

NOMINAL CONDUCTOR AREA (MM2)	NBR OF CORES	KIT REF	CABLE DIAMETER		RESIN VOLUME		
			Min (mm)	Max (mm)	Grammes	cc	Litres
1.5	2	BK1	8	26	190	173	0.174
	3	BK1					
	4	BK1					
2.5	2	BK1	8	26	190	173	0.174
	3	BK1					
	4	BK1					
4	2	BK1	8	26	190	173	0.174
	3	BK1					
	4	BK2	14	32	440	400	0.403
6	2	BK2	14	32	440	400	0.403
	3	BK2					
	4	BK2					
10	2	BK2	14	32	440	400	0.403
	3	BK2					
	4	BK2					
16	1	BK2	14	32	440	400	0.403
	2	BK2					
	3	BK3	23	37	740	673	0.677
	4	BK3					
25	1	BK2	14	32	440	400	0.403
	2	BK2					
	3	BK3	23	37	740	673	0.677
	4	BK4					
35	1	BK2	14	32	440	400	0.403
	2	BK3					
	3	BK4	28	51	1280	1164	1.171
	4	BK4					
50	1	BK2	14	32	440	400	0.403
	2	BK3					
	3	BK4	28	51	1280	1164	1.171
	4	BK4					