



### FEATURES:

- Designed for older Amprobe meters requiring a banana plug tip extended to the bottom on the sheathed insulator.
- Probe body incorporates a two step mold process. First step is Polypropylene for probe rigidity. Second step is Santoprene rubber for handling comfort, added insulation protection and wire strain relief.
- Probe test leads are designed with over-voltage spike protection of up to 6kV.
- Probe body and banana plug are molded directly to the wire for robust pull strength.
- Wire is a high strand count silicone wire for extreme flexibility and high temperature resistance.
- Nickel plated brass tip features high conductivity for precision measurements.
- Banana plug spring is nickel-plated beryllium copper for long insertion life.

### MATERIALS:

Probe Body: Santoprene Rubber (Color: Gray) Over Polypropylene: Fire Retardant  
(Color: One Black, One Red)

Tip: Brass, Nickel plated

Wire: 18 AWG, 65 x 36 Tinned Copper Strand, Silicone Insulation, O.D. .144" (3,66 mm)

Banana Plug: Body – Brass, Nickel Plated

Spring – Beryllium Copper, Nickel Plated

Insulation – Polypropylene, Color: One Black, One Red

### RATINGS:

Operating Voltage: 1000 VRMS/DCCurrent: **10 Amperes**

### ORDERING INFORMATION: Model 5516A

Includes a set of one black and one red test probe

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA