

Black rubber tyred steel centre wheel and castors

- Black rubber tyre (85 shore A ± 3) on a steel centre.
- Plain or roller bearing bore.
- Standard duty loads.
- Zinc plated pressed steel castor housing.
- Suitable for use on compact floors eg cement, stone tiles, metallic, epoxy resins etc.
- Suitable for humid environments and outdoor use.
- Not recommended for use with organic solvents, chlorinated substances, hydrocarbons and mineral oils.
- Conductive wheel has an earthing resistance below 0.1m ohm in accordance with ISO 22878:2004
- Temperature -20°C to +60°C
- ISO2175

Plain Bore Wheel with Nylon Bush



Wheel Size	Bore	Wheel Dia	Wheel Dia	Castor Dia	Castor Dia	Castor Dia	Weight (Kg)	Product Code
80	25	12	34	260	60	65	0.17	531101
100	30	12	34	300	75	80	0.28	531102
125	37.5	15	44	330	85	130	0.51	531103
140	37.5	15	44	340	95	150	0.64	531104
150	40	15	44	350	100	170	0.73	531111
160	40	20	58	370	120	180	1.00	531110
180	45	20	58	390	130	200	1.33	531105
200	50	20	58	410	140	230	1.75	531106
200	50	25	58	410	140	230	1.74	531206
225	50	20	58	420	160	250	2.16	531107
250	60	25	73	500	175	300	3.24	531108
280	60	25	73	550	200	390	3.92	531109

Roller Bearing Wheel



Wheel Size	Bore	Wheel Dia	Wheel Dia	Castor Dia	Castor Dia	Castor Dia	Weight (Kg)	Product Code
80	25	12	34	260	60	65	0.19	533101
100	30	12	34	300	75	80	0.31	533102
125	37.5	15	44	330	85	130	0.54	533103
140	37.5	15	44	340	95	150	0.66	533104
150	40	15	44	350	100	170	0.76	533111
160	40	20	58	370	120	180	1.07	533110
180	45	20	58	390	130	200	1.39	533105
200	50	20	58	410	140	230	1.81	533106
200	50	25	58	410	140	230	1.78	533206
225	50	20	58	420	160	250	2.42	533107
250	60	25	73	500	175	300	3.14	533108
280	60	25	73	550	200	390	3.84	533109

Conductive and Anti-static Roller Bearing Wheel



Wheel Size	Bore	Wheel Dia	Wheel Dia	Castor Dia	Castor Dia	Castor Dia	Weight (Kg)	Product Code
80	25	12	34	260	60	65	0.19	533101AS
100	30	12	34	300	75	80	0.31	533102AS
125	37.5	15	44	330	85	130	0.54	533103AS
140	37.5	15	44	340	95	150	0.66	533104AS
150	40	15	44	350	100	170	0.76	533111AS
160	40	20	58	370	120	180	1.07	533110AS
180	45	20	58	390	130	200	1.39	533105AS
200	50	20	58	410	140	230	1.81	533106AS
200	50	25	58	410	140	230	1.78	533206AS
225	50	20	58	420	160	250	2.42	533107AS
250	60	25	73	500	175	300	3.14	533108AS
280	60	25	73	550	200	390	3.84	533109AS



Black rubber tyred steel centre wheel and castors

Standard Duty Swivel Castor



⊙	⊥	↻	⊥	⊥	↻	⊥	⊥	⊥	⊥	⊥	⊥	⊥
80	25	107	100x85	80x60	9	39	65	0.69	535001	0.70	535101	
100	30	128	100x85	80x60	9	37	80	0.82	535002	0.84	535102	
125	37.5	156	100x85	80x60	9	39	130	1.18	535003	1.21	535103	
140	37.5	176	100x85	80x60	9	37	150	1.31	535004	1.34	535104	
150	40	182	100x85	80x60	9	37	170	1.42	535011	1.45	535111	
160B	40	187	100x85	80x60	9	50	180	1.75	535012	1.81	535112	
160	40	199	140x110	105x80	11	56	180	2.44	535010	2.50	535110	
180	45	219	140x110	105x80	11	56	200	2.78	535005	2.85	535105	
200	50	240	140x110	105x80	11	56	230	3.25	535006	3.31	535106	
225	50	263	140x110	105x80	11	56	250	3.67	535007	3.93	535107	
250	60	296	200x160	160x120	14	87	300	6.66	534708	6.56	534908	
280	60	311	200x160	160x120	14	87	390	7.35	534709	7.27	534909	

Standard Duty Fixed Castor



⊙	⊥	↻	⊥	⊥	↻	⊥	⊥	⊥	⊥	⊥	⊥	⊥
80	25	107	100x85	80x60	9	65	0.49	535701	0.51	535901		
100	30	128	100x85	80x60	9	80	0.62	535702	0.65	535902		
125	37.5	156	100x85	80x60	9	130	0.92	535703	0.95	535903		
140	37.5	176	100x85	80x60	9	150	0.93	535704	0.96	535904		
150	40	182	100x85	80x60	9	170	1.04	535711	1.07	535911		
160B	40	187	100x85	80x60	9	180	1.55	535712	1.61	535912		
160	40	199	140x110	105x80	11	180	2.07	535710	2.13	535910		
180	45	219	140x110	105x80	11	200	2.49	535705	2.56	535905		
200	50	240	140x110	105x80	11	230	2.89	535706	3.05	535906		
225	50	263	140x110	105x80	11	250	3.18	535707	3.45	535907		
250	60	296	200x160	160x120	14	300	5.16	535708	5.06	535908		
280	60	311	200x160	160x120	14	390	5.84	535709	5.76	535909		

Standard Duty Swivel Castor with Foot Brake



⊙	⊥	↻	⊥	⊥	↻	⊥	⊥	⊥	⊥	⊥	⊥	⊥
80	25	107	100x85	80x60	9	39	120	65	0.87	535401	0.89	535421
100	30	128	100x85	80x60	9	37	120	80	1.00	535402	1.03	535422
125	37.5	156	100x85	80x60	9	39	120	130	1.30	535403	1.33	535423
140	37.5	176	100x85	80x60	9	37	120	150	1.46	535404	1.49	535424
150	40	182	100x85	80x60	9	37	120	170	1.57	535411	1.60	535431
160	40	199	140x110	105x80	11	56	156	180	2.69	535410	2.75	535430
180	45	219	140x110	105x80	11	56	156	200	3.07	535405	3.13	535425
200	50	240	140x110	105x80	11	56	156	230	3.39	535406	3.45	535426
225	50	263	140x110	105x80	11	56	156	250	3.95	535407	4.22	535427

● For further accessories including threadguards, axle material, threaded stems, solid plugs and whatever you cannot find please contact us. For expanders see page 160.

Black rubber tyred steel centre wheel and castors

Standard Duty Bolt Hole Swivel Castor



Castor Size	Wheel Dia	Stem Dia	Stem Length	Stem Dia	Stem Length	Stem Dia	Weight (kg)	Part No.	Weight (kg)	Part No.
73	25	107	12	80	39	65	0.61	537701	0.63	537901
100	30	128	12	80	37	80	0.74	537702	0.76	537902
125	37.5	156	12	80	39	130	1.09	537703	1.12	537903
140	37.5	176	12	80	37	150	1.23	537704	1.26	537904
150	40	182	12	80	37	170	1.35	537711	1.38	537911
160	40	193	20	102	56	180	1.78	537710	1.85	537910
180	45	214	20	102	56	200	2.66	537705	2.73	537905
200	50	236	20	102	56	230	3.16	537706	3.22	537906

Standard Duty Bolt Hole Castor with Foot Brake



Castor Size	Wheel Dia	Stem Dia	Stem Length	Stem Dia	Stem Length	Weight (kg)	Part No.	Weight (kg)	Part No.	
73	25	107	12	80	39	120	0.78	538201	0.80	538221
100	30	128	12	80	37	120	0.94	538202	0.96	538222
125	37.5	156	12	80	39	120	1.24	538203	1.27	538223
140	37.5	176	12	80	37	120	1.38	538204	1.41	538224
150	40	182	12	80	37	120	1.49	538211	1.52	538231
160	40	193	20	102	56	156	2.04	538210	2.10	538230
180	45	214	20	102	56	156	3.95	538205	3.01	538225
200	50	236	20	102	56	156	3.29	538206	3.35	538226

Swivel Castor with Central Pedal Brake *



Castor Size	Wheel Dia	Stem Dia	Stem Length	Stem Dia	Stem Length	Weight (kg)	Part No.	Weight (kg)	Part No.			
160	40	197	140x110	105x80	11	56	40	33	15	180	1.56	O.A.
200	50	240	140x110	105x80	11	56	40	33	15	230	3.45	534806

* These are commonly used on 1100 cu. lit. waste containers. Please note there are a number of small specification changes to suit different waste container manufacturers. Threaded stem & solid plug fitting are available to be fitted with bolt hole castor.

Directional Lock - fits underside of top plate

Castor Size	Wheel Dia	Stem Dia	Stem Length	Pedal width	Pedal length	Pedal stroke	Weight (kg)	Part No.
160	40	80/75	11	49	120	36	0.37	401215
200	50	80/75	11	49	120	36	0.37	401215

For further accessories including threadguards, axle material, threaded stems, solid plugs and whatever you cannot find please contact us. For expanders see page 160.

