

## USB & Firewire Combo Products

### USB2 - 33COMBO & USB2 - PCICOMBO

**Tel:**  
**01773 514514**

**Fax:**  
**01773 514515**

**E-Mail:**  
Sales@cablesdirect.co.uk



USB & FireWire Combo  
Host Card (PCI)



USB Line Extender



Share-A-Hub

**Cables Direct Ltd,**  
**Unit C,**  
**Heage Road**  
**Industrial Estate,**  
**Heage Road,**  
**Ripley,**  
**Derbyshire,**  
**DE5 3GH.**

**Registered in England**  
**No. 2819039**



**ISSUE No: 1**


USB Universal Serial Bus

Our new range of USB 2.0 and IEEE 1394a (Firewire 400) products, allow users to have both USB 2.0 and IEEE 1394a connection types on one PCI Card and 5.25 / 3.5 Bay depending on model. Running at 480 Mbps the USB connection is slightly faster than the Firewire connection, but both have there different uses.



**USB2-33COMBO**

PCI Card has 2x External USB 2.0 Ports and 1x External Firewire (IEEE-1394) 6 Pin  
5.25" or 3.5" Bay has 2x USB 2.0 Ports and 1x 6 Pin + 1x 4 Pin Firewire (IEEE-1394A) Ports



**USB2-PCICOMBO**

PCI Card has 2x External & 2x Internal USB 2.0 Ports and 1x 4 Pin and 1x 6 Pin External Firewire (IEEE-1394)

#### Retail Packaging



#### USB 2.0 Features.

- **VIA Chipset for PC use only**
- Compliant with Universal Serial Bus Revision 2.0
- Supports Data Transfer Rates of 1.5/12/480 Mbps
- Compliant with Open Host Controller Interface Specification for USB Revision 1.1
- Compliant with Enhanced Host Controller Interface Specification USB 2.0 Revision 0.95
- Root Hub with 4 downstream facing ports. (Type A Socket, External and Internal/On hub depending on model)
- Hot-Plug feature allows you to connect/disconnect devices without powering down the system.
- 32-Bit 33 Mhz host interface compliant to PCI Specification release 2.2
- Supports PCI-Bus Power Management interface Specification release 1.1
- Max. 5v/500 mA Power Supply
- Supports Windows 98/SE/2000/ME/XP (Needs Service Pack 1)

#### IEEE 1394A Features.

- IEEE 1394a (Firewire 400) with data transfer rates of up to 400Mb/s.
- Complies with Standard for IEEE 1394 High Performance Serial Bus.
- Works with many DV Camcorders for digital video creating/editing.
- Hot-Plug feature allows you to connect/disconnect devices without powering down the system.
- Provides 3x Sockets for USB2-33COMBO (1x 6 Pin = PCI Card, 1x 4 Pin & 1x 6 Pin on Drive Bay) Or 2x ( 1x 4 Pin & 1x 6 Pin) Sockets for USB2-PCICOMBO
- Supports Plug and Play specification
- Connect up to 63 devices

USB2 - 33COMBO	Combo USB 2.0 & IEEE 1394a PCI Card and 5¼" or 3½" Combo Drive Bay Hub
USB2 - PCICOMBO	Combo USB 2.0 & IEEE 1394a PCI Card