



E I DUPONT DE NEMOURS & CO INC
 DUPONT POLYMERS, ENGINEERING POLYMERS
 NYLON RESINS PO BOX 80713, CHESTNUT RUN
 PLAZA, WILMINGTON DE 19880

E41938 (M)



MHDsg	Col	Min Thk mm	UL94 Flame Class	Elec	RTI		H W	H A	H V	D T	C
					Mech with Imp	Mech w/o Imp					
Polyamide, Type 66 nylon (PA66), designated "Zytel", furnished in the form of pellets.											
132F	AH	0.71	94V-2	126	86	85	4	0	—	—	—
133J, 135F	AH	16	94V-2	126	76	85	3	0	0	—	—
		30	94V-2	126	76	85	2	0	0	6	0
		80	94V-2	126	76	85	2	0	0	—	—
✓101(H) 101F, 101L, E101L, E101(H)	AH	0.71	94V-2	126	86	85	4	0	—	—	—
		16	94V-2	126	76	85	3	0	0	—	—
101(H) 101F, 101L, E101L, E101(H) LFE1068	AH	30	94V-2	126	76	85	2	0	0	6	0
		80	94V-2	126	76	85	2	0	0	—	—
		0.71	94V-2	126	—	—	4	0	—	—	—
LFE1030	AH	16	94V-2	126	76	85	3	0	0	—	—
		30	94V-2	126	76	85	2	0	0	6	0
		80	94V-2	126	76	85	2	0	0	—	—

300-8976

TOLERANCE: L ≤ 10 ± 0.2 10 < L ≤ 30 ± 0.3 30 < L ≤ 50 ± 0.5 50 < L ≤ 100 ± 0.7 100 < L ≤ 250 ± 1.2 ABOVE 250 ± 1.5	APPROVED BY 	MATERIAL: NYLON 66(UL) FLAME CLASS: 94V-2 COLOR: NATURAL	品固企業有限公司 品基電子塑膠製品廠 PINGOOD ENTERPRISE CO., LTD.		
	REVIEWED BY 		PART NAME: LED套 LED HOLDER		REV. 1
	DRAWN BY 		PART NO.: LEDX-10		SIZE A
	UNIT mm		SCALE 5.5:1	SHEET 1 OF 1	