


8205 Paired - Audio Wire and Cable

	<p style="text-align: center;">For more information please call 1-800-Belden1</p> <p style="text-align: center;"><u>See Put-ups and Colors</u></p> <p style="text-align: center;">Color Code Chart : No. 3 for Paired Cables (Belden Standard).pdf</p>
---	---

Description:

20 AWG stranded (7x28) tinned copper conductors, twisted pairs, PVC insulation, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	20
Stranding	7x28
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Nom. Insulation Wall Thickness	.013 in.

PAIR:

Pair Color Code Chart :

Number	Color
1	Black & Red

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.025 in.

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.180 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +80°C
Bulk Cable Weight	15.3 lbs/1000 ft.

8205 Paired - Audio Wire and Cable

Max. Recommended Pulling Tension	28 lbs.
Min. Bend Radius (Install)	2 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMG
CEC/C(UL) Specification	CMG

FLAME TEST:

C(UL) Flame Test	FT4
------------------	-----

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Capacitance Conductor to Conductor @ 1 KHz	24.5 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	10.0 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS
Other Maximum Continuous Currents	3.7 Amps per conductor @ 20°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8205 060100	1 PR #20 PVC FRPVC	100	2.6	CHROME	
8205 0601000	1 PR #20 PVC FRPVC	1000	18	CHROME	C
8205 060500	1 PR #20 PVC FRPVC	500	9	CHROME	
8205 060U1000	1 PR #20 PVC FRPVC	U1000	17	CHROME	
8205 060U500	1 PR #20 PVC FRPVC	U500	9	CHROME	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 10-15-2003

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.