




SX70/SX80 De-Soldering Endura Tips



- Tips last up to twice as long as conventional desoldering tips
- Requires less maintenance and cleaning than existing tips, saving time
- Allows for continuous workflow
- Supplied in packs of 5

3228563

| Tip | Description | Size | Mftrs. List No. |
|-----------------------------------------------------------------------------------|--------------|---------------------------------------------|-----------------|
| Recommended for Thru-Hole Desoldering | | | |
|  | Thermo-Drive | 0.030" (0.76mm) I.D. x 0.080" (2.03mm) O.D. | 1121-0625-P5 |
| | Thermo-Drive | 0.040" (1.02mm) I.D. x 0.090" (2.29mm) O.D. | 1121-0624-P5 |
| | Thermo-Drive | 0.060" (1.52mm) I.D. x 0.120" (3.05mm) O.D. | 1121-0626-P5 |
| | Thermo-Drive | 0.090" (2.29mm) I.D. x 0.200" (5.1mm) O.D. | 1121-0627-P5 |
| Recommended for Thru-Hole Desoldering in Tight Areas | | | |
|  | Precision | 0.020" (0.5mm) I.D. x 0.070" (1.79mm) O.D. | 1121-0680-P5 |
| | Precision | 0.030" (0.76mm) I.D. x 0.080" (2.03mm) O.D. | 1121-0678-P5 |
| | Precision | 0.040" (1.02mm) I.D. x 0.090" (2.29mm) O.D. | 1121-0679-P5 |
| | Precision | 0.060" (1.52mm) I.D. x 0.110" (2.79mm) O.D. | 1121-0690-P5 |
| Recommended for Surface Mount Land and Via Desoldering | | | |
|  | Flo-D-Sodr | 0.060" (1.52mm) I.D. x 0.188" (4.78mm) O.D. | 1121-0631-P5 |