



NOTES: UNLESS OTHERWISE SPECIFIED

1. BODIES: BRASS PER JIS-C3604
2. CENTER CONTACT: BRASS PER JIS-C3604
3. INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710
4. CONNECTOR INTERFACE PER MIL-STD-348A
5. PART TO BE CLEAN AND FREE OF BURRS

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
5	BODY	BRASS	1	GOLD 3 μ" MIN.
4	CENTER CONTACT	BRASS	1	GOLD 30 μ" MIN.
3	INSULATION	TEFLON	1	NONE
2	WASHER	BRASS	1	GOLD 3 μ" MIN.
1	NUT	BRASS	1	GOLD 3 μ" MIN.

製圖	DRAWN	TOLERANCE	品名	24-16-1 (50Ω)	日期	DATE	版次	REV.
	袁金玉							
檢圖	CHECK	.XX ±0.1	單位	DWG.NO.	24-0005			
	袁金華	.XXX ±0.05						
認定	APPROVAL	蘇文申	比例	佳楠精密電子股份有限公司 CHIN NAN PRECISION ELECTRONICS CO.,LTD.				
	蘇文申	ANGLE ±5°						