

Pair colours:	1 x red/1 x blue - 1.00mm diameter	
Screen:	80 x 0.10mm close lap spiral high purity OFC	
Overall jacket:	Abrasion resistant anti-kink PVC/Neoprene composite	
Sheath colour:	Black - RAL 9005	Green - RAL 6001
	Blue - RAL 5002	Grey - RAL 7031
	Red - RAL 3001	Yellow - RAL 1021
	White - RAL 9010	Orange - RAL 2009
	Brown - RAL 8012	Purple - RAL 4004
Temp. range:	-25°C ~ +70°C	
D.C. resistance:	< 84W/km	
Capacitance:	< 100pF per metre core to core	
	< 165pF per metre cores to screen	
Voltage rating:	250V	
Weight:	50kg/km	
O.D:	6.35mm ±0.15mm	
Drum size:	100m & 300m (maximum length)	
Construction:	Twin conductors of plain (non-tinned) Oxygen Free Copper with cross linked polyethylene (XLPE) insulation twisted together with natural cotton fillers underneath a tightly lapped spiral OFC screen. Oversheathed with a very flexible matt PVC/Neoprene anti-kink outer jacket.	

Available cut to any length. Priced per metre.

E-mail: webmaster@vdc trading.com Call: +44 (0)20 7700 2777 (8.00 am - 6.00 pm)
All contents © VDC Trading Ltd. All rights reserved