


H07RN-F Cable

PRO-POWER
Quality Cables



- Flexible, single and multi-core insulated and sheathed cable
- H07RN-F 450/750V part 4 and HD 22.4 S3 and DIN VDE 0282 part 4
- Voltage rated: 450/750V rms
- Ethylene propylene rubber sheath, type EI 4
- Operating temperature: -25 to 60°C
- Flexible tinned copper conductors
- Ideal for water pumps, portable equipment or machine tools

Number of cores	Current Rating	CSA	Nominal Outside Dia
2	24A	1.5mm ²	8.9mm
2	33A	2.5mm ²	10.6mm
3	24A	1.5mm ²	9.5mm
3	33A	2.5mm ²	11.3mm
3	45A	4.0mm ²	13.0mm
4	22A	1.5mm ²	10.4mm
4	30A	2.5mm ²	12.5mm
4	40A	4.0mm ²	14.3mm

337898

Order Code	CSA	Reel Size	Price Per Reel	
			1+	5+
2 core				
476-8395	1.5mm ²	50m	39.45	36.00
476-8401	1.5mm ²	100m	79.57	72.54
476-8413	2.5mm ²	50m	61.00	55.97
476-8425	2.5mm ²	100m	122.45	110.00
3 core				
476-8437	1.5mm ²	50m	45.37	41.12
476-8449	1.5mm ²	100m	90.97	82.69
476-8450	2.5mm ²	50m	66.45	60.10
476-8462	2.5mm ²	100m	132.05	120.63
476-8474	4.0mm ²	50m	100.97	92.80
476-8486	4.0mm ²	100m	202.63	185.00
4 core				
476-8498	1.5mm ²	50m	55.14	49.80
476-8504	1.5mm ²	100m	110.45	100.21
476-8516	2.5mm ²	50m	80.25	74.00