

Dialight

586 Series

Single Chip BASED LED

T 3 1/4 MINIATURE BAYONET (BA9S)




FEATURES / BENEFITS

- ▲ High brightness with low current draw - uses up to 90% less energy than incandescent
- ▲ Long life - up to 100K hours
- ▲ True non-polarized configurations available
- ▲ No heat generated
- ▲ Mounts directly into industry-standard socket
- ▲ Resistant to shock and vibration
- ▲ AllInGaP and InGaN technology
- ▲ Super bright single chip design
- ▲ Colors include red, green, amber, blue and white

Dialight's line of based LED lamps is designed to directly replace many popular subminiature and miniature incandescent lamps. The benefits of LED technology over incandescent are significant: They offer long life, are shock resistant, withstand vibration and provide energy conservation.

SPECIFICATIONS



Measurements are typical
Dimensions are inches [mm]

- ▲ Operating Voltages - 6, 14, and 28 VDC
- ▲ Polarized and non-polarized available*
- ▲ Operating temperature: -30°C to 85°C
- ▲ Storage temperature: -40°C to 100°C
- ▲ Replaces incandescent lamp numbers: 44, 47, 313, 755, 1815, 1819, 1847, 1850, 1866, 1889, 1891, 1892, 1893 and 1895**

* If the socket's polarity is unknown, Dialight recommends using a non-polarized lamp.

** May replace other incandescent lamps.

CONSIDERATIONS

- ▲ Since lens caps act as filters for the light emitted from the based LED, it is important to match the color of the wavelength of the LED. Dialight recommends using transparent lenses, which will optimize light output.
- ▲ These lamps are available in 6, 14, and 28 VDC. For 120 VAC products please see the 585 Series Cluster lamp.
- ▲ Although these lamps can be operated at a lower voltage, which will increase the life, the intensity will be reduced.
- ▲ Operation of the based LED at a higher voltage should not exceed 10% above the recommended voltage.
- ▲ Dialight does not recommend that based LED lamps be used in neon sockets.

Dialight reserves the right to make changes at any time in order to supply the best product possible.



Dialight Corporation
1501 Route 34 South • Farmingdale, NJ 07727 USA
Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com



a Roxboro Group Company

MDEL586E001_B

T 3 1/4 MINIATURE BAYONET (BA9S) POLARIZED

Part Number	Color	Peak Wavelength (nm)	Nominal Voltage	Forward Current (TYP. - mA)	Intensity (TYP. - mcd)	Can be used in place of Multi-Chip Part Number
586-2401-101	Red	630	6	15	1050	585-4111
586-2402-101	Green	525	6	15	1650	585-4311
586-2403-101	Yellow	592	6	15	1275	585-4411
586-2405-101	Blue	470	6	15	487	-
586-2406-101	White	*	6	15	825	-
586-2401-103	Red	630	14	15	1050	585-4113
586-2402-103	Green	525	14	15	1650	585-4313
586-2403-103	Yellow	592	14	15	1275	585-4413
586-2405-103	Blue	470	14	15	487	-
586-2406-103	White	*	14	15	825	-
586-2401-105	Red	630	28	15	1050	585-4115
586-2402-105	Green	525	28	15	1650	585-4315
586-2403-105	Yellow	592	28	15	1275	585-4415
586-2405-105	Blue	470	28	15	487	-
586-2406-105	White	*	28	15	825	-

*Color Coordinates: x = 0.330, y = 0.365

T 3 1/4 MINIATURE BAYONET (BA9S) NON-POLARIZED

Part Number	Color	Peak Wavelength (nm)	Nominal Voltage	Forward Current (TYP. - mA)	Intensity (TYP. - mcd)	Can be used in place of Multi-Chip Part Number
586-2401-201	Red	630	6	15	1050	585-4121
586-2402-201	Green	525	6	15	1650	585-4321
586-2403-201	Yellow	592	6	15	1275	585-4421
586-2405-201	Blue	470	6	15	487	-
586-2406-201	White	*	6	15	825	-
586-2401-203	Red	630	14	15	1050	585-4123
586-2402-203	Green	525	14	15	1650	585-4323
586-2403-203	Yellow	592	14	15	1275	585-4423
586-2405-203	Blue	470	14	15	487	-
586-2406-203	White	*	14	15	825	-
586-2401-205	Red	630	28	7.5	525	585-4125
586-2402-205	Green	525	28	7.5	825	585-4325
586-2403-205	Yellow	592	28	7.5	637	585-4425
586-2405-205	Blue	470	28	7.5	243	-
586-2406-205	White	*	28	7.5	412	-

*Color Coordinates: x = 0.330, y = 0.365

Based LEDs SELECTION

With the technological advancements in Light Emitting Diodes (LEDs) brightness can now rival the incandescent lamp when used in similar packages. These advancements have created a new type of product called the based LED - an LED with the functionality of an incandescent bulb.

The following styles are currently available in red, green, amber, blue and white:

- ▲ T 1 3/4 Midget Flange
- ▲ T 1 3/4 Bi-Pin
- ▲ T 1 3/4 Wedge (T5)
- ▲ T 2 Telephone Slide
- ▲ T 3 1/4 Miniature Bayonet (BA9S)
- ▲ T 3 1/4 Miniature Screw (E10)
- ▲ T 3 1/4 Wedge (T10)
- ▲ 15mm SC Bayonet (BA15S)

Dialight's line of based LEDs continues to grow. Please visit our website for more information.

www.dialight.com



1501 Route 34 South • Farmingdale, NJ 07727 USA

Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com



a Roxboro Group Company

MDEL586E001_B