

DVI Video Leads



A comprehensive range of professional quality DVI interconnection leads that are manufactured and support the standards laid down by the DDWG (Digital Display Working Group). The DVI-D and DVI-I cables are all dual link cables, which can be used for both single and dual link applications. Dual link DVI are compatible with all graphics cards to TFT/LCD monitor applications.

- Single link types can support UXGA (1600x1200) displays
- Dual link types can support QXGA (2048x1536) displays
- Future proof for dual link (QXGA) applications
- Overmoulded connector construction

DVI-I: Supports analogue and digital TMDS transmissions

DVI-D: supports 1.6Gbit/sec transmission rates

DVI-A: supports 2.5GHz analogue RGB bandwidths

333678

Length	Order Code
DVI-D Male to Male – Dual Link	
1m	470-5270
2m	470-5282
3m	470-5294
5m	470-5300
DVI-D Male to Female – Dual Link	
3m	470-5312
5m	470-5324
DVI-I Male to Male – Dual Link	
1m	470-5336
2m	470-5348
3m	470-5350
5m	470-5361
10m	470-5373
DVI-I Male to Female – Dual Link	
5m	470-5385
10m	470-5397
DVI-A Male to VGA Male	
2m	470-5415
3m	470-5427

5m	470-5439
DVI-A Male to 5x BNC Male	
2m	470-5440
DVI-I Male to VGA Female	
Adaptor	470-5403