


Material Specifications

Insulating material		Polyamide
IRC		600 V
Flammability	UL94	V0
	NF F 16 101	I2F2
	Needle flame test IEC 60695-11-5	Compliant

Connecting capacity per clamp

1 Rigid conductor		0.2-4 mm²		24-10 AWG
1 Flexible conductor without ferrule		0.22-4 mm²		24-10 AWG
1 Flexible conductor with ferrule		0.22-4 mm²		24-12 AWG
Ferrule maximum outer diameter		5.5 mm		0.216 in

Multi Connecting capacity per clamp

2 Rigid conductors		0.2-1 mm²		24-18 AWG
2 Flexible conductors without ferrule		0.22-1 mm²		24-18 AWG
2 Flexible conductors with twin ferrule		0.22-1.5 mm²		24-16 AWG

Don't mix **solid and flexible** conductors **in the same clamp**

Don't mix **solid or flexible** conductors of different sizes **in the same clamp**

The "Connecting capacity with ferrule " data is guaranteed with ABB crimping tool PS-3

Cross section

Rated cross section		4 mm²		10 AWG
Maximum Cross section	Manufacturer data	4 mm²	Manufacturer data	10 AWG

Gauge **A3-B3 / 3 mm / 0.118 in / IEC 60947-7-1**

Electrical characteristics

Current

Rated current		IEC 60947-7-1	6.3 A
	Field and factory wiring Cat.2	UL 1059	6.3 A
	Factory wiring Cat.1	UL 1059	6.3 A
		CSA-C-22.2 n° 158	6.3 A
Rated short-time withstand current 1 s (I _{cw})			480 A
Short-time withstand current	0.5 s	Manufacturer data	
	5 s	Manufacturer data	
	10 s	Manufacturer data	
	30 s	Manufacturer data	
	1 mn	Manufacturer data	
Rated short circuit withstand		CSA-C-22.2 n° 158	
Max. current (45° temperature increase) / Max. cross section (mm ²)		Manufacturer data	6.3 A 4 mm²
Maximum short circuit current (1s)		Manufacturer data	480 A

Short Circuit Current Rating (SCCR) SA UL 1059 supplement

SCCR UL 1059



With the following configurations:

Maximum voltage	
Suitable conductor wire range	
Fuse rating	
Fuse designation	
Fuse manufacturer name	
Fuse type	
Short circuit current	

Voltage		
Rated voltage	IEC 60947-1	250 V
Rated voltage	UL 1059	150 V
Use Group	UL 1059	D
Rated voltage	CSA-C-22.2 n° 158	150 V
Rated voltage Ex e	IEC/EN 60079-11	
Rated impulse withstand voltage		6000 V
Dielectric test voltage		1890 V
Pollution degree	IEC 60947-1	3
Overtoltage category	IEC 60947-1	III

Dissipated power	
Maximum dissipated power at rated current	IEC





Rated power dissipation at an ambient temperature of 23 °C - IEC 60947-7-3

Overload and short-circuit protection Separate arrangement		2.5 W
Exclusive short-circuit protection Separate arrangement	1 fuse and 4 feed-through blocks	4 W
Overload and short-circuit protection Compound arrangement		2.5 W
Exclusive short-circuit protection Compound arrangement	5 fuse blocks	4 W

Temperature range

Ambient temperature min/max	Storage	-55 +110 °C	<i>-67 +230 F</i>
	Installing	-5 +40 °C	<i>-23 +104 F</i>
	Service	IEC 60068-2-1 -55 +110 °C	<i>-67 +230 F</i>
		EN 60079-7	

Current Derating curve for continuous service temperature



Environmental Characteristics

Additional climatic tests

Dry heat	Conditions	IEC 60068-2-2	Compliant	
		Temperature	+100 °C	
		Duration of test	96 h	
Cyclic damp heat	Conditions	IEC 60068-2-30	Compliant	
		Temperature	+55 °C	
		Number of cycles	2	
Cold	Conditions	IEC 60068-2-1	Compliant	
		Temperature	-40 °C	
		Duration of test	96 h	
Z/ABDM climatic sequence	Conditions	IEC 60068-2-61	Compliant	
		Dry heat Duration of test / Temperature	16 h	+85 °C
		Cyclic damp heat Number of cycles / Temperature	1	+55 °C
		Cold Duration of test / Temperature	2 h	-25 °C

Corrosion

Salt mist	Conditions	IEC 60068-2-11	Compliant	
		Duration of test	96 h	
		Concentration	5 %	
SO ₂	Conditions	ISO 6988	Compliant	
		Duration of test	48 h	
		Concentration	0.2 dm³	
Sulfur dioxide	Conditions	IEC 60068-2-42		
		Duration of test		
Hydrogen sulfur	Conditions	IEC 60068-2-43		
		Duration of test		
Flowing mixed gas corrosion test	Conditions	IEC 60068-2-60		
		Number of the test method		
		Duration of test		

Vibrations

Vibrations	Conditions	IEC 60068-2-6	Compliant	
		Frequency range	10-55 Hz	
		Number of cycles	10	
		Amplitude		
		Acceleration	10 m/s²	
Random vibrations and climatic sequence	Conditions	IEC 60068-2-64		
		Duration of test		
		Frequency range		
		Acceleration		
	Climatic cycles			
	Step 1 -> Temperature / Duration of test			
	Step 2 -> Temperature / Duration of test			
	Temperature variation per minute			

ZS4-SF-T Terminal Block Accessories Compatibility

Description	Type	Order Code	Pack ^(ing) pieces	Weight g (1 pce)	Technical Datasheet PDF
1 End Stops	BAM3	1SNK 900 001 R0000	50	13.80	1SNK 160 026 D0201
2 Jumper Bars	JB6-2	1SNK 906 302 R0000	50	1.30	1SNK 160 029 D0201
	JB6-3	1SNK 906 303 R0000	50	2.10	1SNK 160 029 D0201
	JB6-4	1SNK 906 304 R0000	50	2.90	1SNK 160 029 D0201
	JB6-5	1SNK 906 305 R0000	50	3.60	1SNK 160 029 D0201
	JB6-10	1SNK 906 310 R0000	20	7.40	1SNK 160 029 D0201
3 Test Adapters	TP2	1SNK 900 203 R0000	20	1.73	1SNK 160 036 D0201
	TP4	1SNK 900 205 R0000	20	2.42	1SNK 160 036 D0201
4 Test Connectors	TC5-R1	1SNK 900 201 R0000	10	5.23	1SNK 160 042 D0201
5 Spacers	ES-TC6	1SNK 900 105 R0000	10	0.80	1SNK 160 042 D0201
6 Test Plugs	FC2.MC	1SNA 107 239 R0300	10	1.00	1SNK 160 036 D0201
7 Tools	PS-3	1SNK 900 650 R0000	1	380.00	1SNK 160 024 D0201
8 Terminal Block Markers	MC612	1SNK 150 000 R0000	22	0.06	1SNK 160 006 D0201
	UMH	1SNK 900 611 R0000	10	0.20	1SNK 160 001 D0201
	PROCAP6	1SNK 900 612 R0000	20	0.79	1SNK 160 013 D0201
	SAT6	1SNK 900 615 R0000	5	6.00	1SNK 160 013 D0201