

Making Light Work For You!

<p>Industrial Panel Mounting LED Indicator</p> <p>Dimensions in mm (Typical) Not to Scale</p> <p>* Red Sleeve Denotes Anode Termination</p>	<p style="text-align: right;">Ø8.1mm Mounting Hole</p> <ul style="list-style-type: none"> • High Intensity, Sunlight Readable LEDs • Range of Colours & Voltages available • Fully potted internally to protect from vibration, shock and water ingress • Brass body for safe use in hazardous areas • Sealed to IP67
--	---

507 / 508 Series

Mean Time Between Failure 90,000 Hours

Operating Temperature Range: -20 to +60°C

Storage Temperature Range: -30 to +85°C

Order Code : 507 – 501 – 04

<p>Series Options :</p> <p>507 – Coloured Diffused Lens</p> <p>508 – Smoked Lens</p>	<p>LED Options : Code – LED Colour / Intensity @ 20 mA</p> <table style="width:100%;"> <tr><td>501 – Red 660nm</td><td>2750 mcd</td></tr> <tr><td>521 – Yellow 590nm</td><td>4800 mcd</td></tr> <tr><td>532 – Green 525nm</td><td>6000 mcd</td></tr> <tr><td>930 – Blue 470nm</td><td>2000 mcd</td></tr> <tr><td>997 – White *</td><td>4000 mcd</td></tr> </table> <p>Intensity figures are typical and apply to discrete LED Package power dissipation (max) 700mW</p>	501 – Red 660nm	2750 mcd	521 – Yellow 590nm	4800 mcd	532 – Green 525nm	6000 mcd	930 – Blue 470nm	2000 mcd	997 – White *	4000 mcd	<p>Voltage Options : Code – Voltage / Current</p> <p>04 – 20mA</p> <p>20 – 5/6 Vdc @ 15/20mA</p> <p>21 – 12 Vdc @ 20mA</p> <p>22 – 24 Vdc @ 20mA</p> <p>23 – 28 Vdc @ 20mA</p> <p>24 – 48 Vdc @ 14mA</p>
501 – Red 660nm	2750 mcd											
521 – Yellow 590nm	4800 mcd											
532 – Green 525nm	6000 mcd											
930 – Blue 470nm	2000 mcd											
997 – White *	4000 mcd											

Materials :

Body and Nut: Bright Nickel Plated Brass
 Lens: Polycarbonate
 Termination: Silver Plated Brass 2.8mm Flat Tags
 Panel Seal: Fluoroelastomer
 Lockwasher: Zinc Plated Steel
 Encapsulation: Alumina Filled Epoxy

Technical Information:

Panel Cutout: 8.1mm
 Min. Mounting Centres: x,y = 14.5mm
 Min/Max Panel Thickness: 1.5-13.0mm
 Mounting Torque: 0.65Nm
 Max. Reverse Voltage: 3Vdc (20mA versions)
 IP Rating: 67

* Typical emission colour:
 x=0.31, y=0.32
 Colour temperature 8000K
 Intensities (Iv) and colour shades of white (x,y coordinates) may vary between LEDs within a

Marl International Limited Ulverston, Cumbria. LA12 7RY England
Tel : + 44 (0) 1229 582430 Fax : + 44 (0) 1229 585155
E-mail : sales@marl.co.uk Website : www.marl.co.uk

The company's services are recognised to the Internationally recognised quality standard BS EN ISO9001:2000

The information above does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. No responsibility can be assumed for inaccuracies or printing errors. Marl International Ltd. reserve the right to alter without notice the specification or any condition of supply for products or service.