



# Safety Control Modules

## AZR 301 AL



### AZR 301 AL

Application:

Stop-category EN 60204:

Inputs:

Evaluation:

Cross short recognition:

Voltage:

Outputs:

Additional outputs:

Switching capacity:

Ambient temperature:

Start condition:

Feedback circuit:

Function display:

Approvals:

### Category 4

Emergency Stop, interlock and safety light curtain\* monitoring

0

2 NC or 1 NC contact selectable relay combination

no

24 VAC/DC, 115 VAC or 230 VAC

3 enabling paths

1 signalling contact

max. 250 VAC / 6 A

- 25 °C ... + 45 °C

automatic or start button

yes, separate terminals

1 x LED




USA CAN

Dimensions (H/W/D):

83 / 45 / 140 mm

\* compatible with most makes of light curtains

## AZR 301 AR



### AZR 301 AR

Application:

Stop-category EN 60204:

Inputs:

Evaluation:

Cross short recognition:

Voltage:

Outputs:

Switching capacity:

Ambient temperature:

Start condition:

Feedback circuit:

Function display:

Approvals:

### Category 3

Emergency Stop and interlock monitoring

0

2 NC or 1 NC contact selectable relay combination

yes

24 VAC, 24 VDC

3 enabling paths

max. 250 VAC / 6 A

- 25 °C ... + 45 °C

automatic or start button

yes, separate terminals

3 x LED



FRG USA CAN

Dimensions (H/W/D):

82 / 22,5 / 99 mm