


# 1N4933/4934/4935/4936/4937

## 0.5A to 6A Axial



### Features:

- Low forward voltage drop.
- High surge current capability.
- High reliability.
- High current capability.
- DO-41 package.



Length = 0.20 (5.2), Diameter = 0.106 (2.7)

Dimensions : Inches (Millimetres)

### 1.0Ampere Fast Recovery Rectifiers

Absolute Maximum Ratings\*

$T_A = 25^\circ\text{C}$  unless otherwise noted.

Symbol	Parameter	Value	Units
$I_O$	Average rectified current 0.375" lead length at $T_A = 50^\circ\text{C}$	1.0	A
$I_{f(\text{surge})}$	Peak forward surge current 8.3ms single half-sine-wave Superimposed on rated load (JEDEC method)	30	
$P_D$	Total device dissipation Derate above $25^\circ\text{C}$	2.5 20	W mW/ $^\circ\text{C}$
$R_{\theta JA}$	Thermal resistance, Junction to ambient	50	$^\circ\text{C}/\text{W}$
$T_{stg}$	Storage temperature range	-50 to +150	$^\circ\text{C}$
$T_J$	Operating junction temperature		

\*These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.



# 1N4933/4934/4935/4936/4937

0.5A to 6A Axial




## Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted


Parameter	Device					Units
	1N4933	1N4934	1N4935	1N4936	1N4937	
Peak repetitive reverse voltage	50	100	200	400	600	V
Maximum RMS voltage	35	70	140	280	420	
DC reverse voltage (Rated $V_R$ )	50	100	200	400	600	
Maximum reverse current at rated $V_R$ $T_A = 25^\circ\text{C}$ $T_A = 100^\circ\text{C}$						$\mu\text{A}$
Maximum reverse recovery time $I_F = 1\text{A}$ , $I_R = 1.0\text{A}$ , $I_{RR} = 0.25\text{A}$						nS
Maximum forward voltage at 1.0A						V
Typical junction capacitance $V_R = 4.0\text{V}$ , $f = 1.0\text{MHz}$						pF

## Typical Characteristics


Forward Current Derating Curve




Forward Characteristics



Non-Repetitive Surge Current



Reverse Characteristics






# 1N4933/4934/4935/4936/4937

0.5A to 6A Axial



Typical Junction Capacitance



Notes:

1. Rise time = 7.0ns maximum; Input impedance = 1.0 Mega $\Omega$  22pF.
2. Rise time = 10ns maximum; Source impedance = 50 $\Omega$ .

Reverse Recovery Time Characteristic and Test Circuit Diagram

## Specifications

$I_{F(av)}$ (A)	$I_{FSM}$ (A)	$t_{rr}$ maximum (ns)	$V_F$ (V)	$I_F$ (A)	Package	Part Number
1	30	150	1.2	1	DO-41	1N4933
						1N4934
						1N4935
						1N4936
						1N4937

Order Multiple = 10



# 1N4933/4934/4935/4936/4937

## 0.5A to 6A Axial



### Notes:

### International Sales Offices:



**AUSTRALIA – Farnell InOne**  
Tel No: ++ 61 2 9645 8888  
Fax No: ++ 61 2 9644 7898



**FINLAND – Farnell InOne**  
Tel No: ++ 358 9 560 7780  
Fax No: ++ 358 9 345 5411



**NETHERLANDS – Farnell InOne**  
Tel No: ++ 31 30 241 7373  
Fax No: ++ 31 30 241 7333



**SWITZERLAND – Farnell InOne**  
Tel No: ++ 41 1 204 64 64  
Fax No: ++ 41 1 204 64 54



**AUSTRIA – Farnell InOne**  
Tel No: ++ 43 662 2180 680  
Fax No: ++ 43 662 2180 670



**FRANCE – Farnell InOne**  
Tel No: ++ 33 474 68 99 99  
Fax No: ++ 33 474 68 99 90



**NEW ZEALAND – Farnell InOne**  
Tel No: ++ 64 9 357 0646  
Fax No: ++ 64 9 357 0656



**UK – Farnell InOne**  
Tel No: ++ 44 8701 200 200  
Fax No: ++ 44 8701 200 201



**BELGIUM – Farnell InOne**  
Tel No: ++ 32 3 475 2810  
Fax No: ++ 32 3 227 3648



**GERMANY – Farnell InOne**  
Tel No: ++ 49 89 61 39 39 39  
Fax No: ++ 49 89 613 59 01



**NORWAY – Farnell InOne**  
Tel No: ++ 45 44 53 66 66  
Fax No: ++ 45 44 53 66 02



**UK – BuckHickman InOne**  
++ 44 8450 510 150  
++ 44 8450 510 130



**BRAZIL – Farnell-Newark InOne**  
Tel No: ++ 55 11 4066 9400  
Fax No: ++ 55 11 4066 9410



**HONG KONG – Farnell-Newark InOne**  
Tel No: ++ 852 2268 9888  
Fax No: ++ 852 2268 9899



**PORTUGAL – Farnell InOne**  
Tel No: ++ 34 93 475 8804  
Fax No: ++ 34 93 474 5288



**UK – CPC**  
++ 44 8701 202 530  
++ 44 8701 202 531



**CHINA – Farnell-Newark InOne**  
Tel No: ++86 10 6238 5152  
Fax No: ++86 10 6238 5022



**IRELAND – Farnell InOne**  
Tel No: ++ 353 1 830 9277  
Fax No: ++ 353 1 830 9016



**SINGAPORE – Farnell-Newark InOne**  
Tel No: ++ 65 6788 0200  
Fax No: ++ 65 6788 0300



**EXPORT – Farnell InOne**  
Tel No: ++ 44 8701 200 208  
Fax No: ++ 44 8701 200 209

For enquiries from all other markets



**DENMARK – Farnell InOne**  
Tel No: ++ 45 44 53 66 44  
Fax No: ++ 45 44 53 66 06



**ITALY – Farnell InOne**  
Tel No: ++ 39 02 93 995 200  
Fax No: ++ 39 02 93 995 300



**SPAIN – Farnell InOne**  
Tel No: ++ 34 93 475 8805  
Fax No: ++ 34 93 474 5107



**ESTONIA – Farnell InOne**  
Tel No: ++ 358 9 560 7780  
Fax No: ++ 358 9 345 5411



**MALAYSIA – Farnell-Newark InOne**  
Tel No: ++ 60 3 7873 8000  
Fax No: ++ 60 3 7873 7000



**SWEDEN – Farnell InOne**  
Tel No: ++ 46 8 730 50 00  
Fax No: ++ 46 8 83 52 62

<http://www.farnellinone.com>

<http://www.buckhickmaninone.com>

<http://www.cpc.co.uk>

**Disclaimer** This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2004.

