

815/ 816/ 817 Installation Permanent/LED/Flashing

Vandal-proof construction withstands every mechanical and natural challenge

High protection rating IP 65

High impact Polycarbonate dome (up to 20 Joules)

Bulb change via rear access with bayonet mechanism

Tamper-proof - bulb change via rear access with bayonet mechanism



Accessories

95501534	<u>Bulb BA 15d, max. 52 mm, 7 W, 12 V</u>
95501535	<u>Bulb BA 15d, max. 52 mm, 7 W, 24 V</u>
95501537	<u>Bulb BA 15d, max. 52 mm, 7 W, 115 V</u>
95501538	<u>Bulb BA 15d, max. 52 mm, 7 W, 230 V</u>
97581201	<u>Tube adapter</u>
97581202	<u>Base for surface mounting</u>
97581503	<u>housing for 1 beacon</u>
97581507	<u>housing for 2 beacon</u>
97581508	<u>housing for 3 beacon</u>
97581522	<u>Anti-twist device</u>
97584010	<u>Base with integrated tube, Ø 25 mm, 110 mm long, plastic</u>
97584025	<u>Tube, Ø 25 mm, all anodized aluminium, 250 mm long</u>
97584040	<u>Tube, Ø 25 mm, all anodized aluminium, 400 mm long</u>
97584510	<u>Tube, Ø 25 mm, all anodized aluminium, 100 mm long</u>
95501537	<u>Bulb BA 15d, max. 52 mm, 7 W, 48 V</u>





Terms and Conditions - Imprint

Werma Signaltechnik GmbH + Co.KG · Dürbheimer Straße 15 · D-78604 Rietheim-Weilheim
Tel. ++49 (0) 74 24 / 95 57-0 · Fax. ++49 (0) 74 24 / 95 57-44 · eMail: info@werma.de