



product details

**OT 6/200-240/24 CE UNV1**

Product description: OT 6/200-240/24 CE UNV1  
 EAN/ Product: 4008321113269  
 Quantity: Unpacked (UNV) contains 1 Piece (PCE)

You can find this product in the eCatalog:  
[http://catalog.myosram.com?~language=EN&~country=COM&it\\_p=4008321113269](http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321113269)

Applications	
Dimmable	Yes <sup>1)</sup>
Type of protection	IP65
Short-circuit protection	automatic reversible
Overload protection	automatic reversible
Overtemperature protection	automatic reversible

General Description	
Design / version	ECG standard
Standards	acc. to IEC 61347-2-2   acc. to IEC 61347-2-13   acc. to IEC 62384   acc. to EN 55015   acc. to IEC 61000-3-2   acc. to IEC 61000-3-3   acc. to IEC 61547
Sstl-Number	4031154

Technical - Electrical Data	
Mains frequency	50-60 Hz
TH full width at half maximum	120 $\mu$ s <sup>2)</sup>
Device power loss	... 1.5 W <sup>3)</sup>
Lamp wattage	6 W <sup>4)</sup>
Power factor c	> 0.50
Nominal voltage	200-240 V
Output voltage	24 $\pm$ 0.8 V
DC voltage	176...264 V
IP inrush current	15 A <sup>5)</sup>
Max. no. of ECGs on circuit breaker 10A	30
Max. no. of ECGs on circuit breaker 16A	48

Technical - Geometries	
Width	50 mm
Height	22 mm
Length	51 mm

Technical - Temperatures	
Max. casing temp. in case of fault	110 °C
Max. operating temp. at the Tc point	70 °C
Ambient temperature range	-20 ... +50 °C
Storage temperature	-40 ... 85 °C
Relative humidity	5 ... 85 % <sup>6)</sup>

Packaging units				
EAN	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321113269	Unpacked contains 1 Piece	57,000 mm x 24,000 mm x 59,000 mm	57,500 g (0,000 g)	0,081 Cubic dec.
4008321113276	Shipping carton box contains 20 Piece	138,000 mm x 76,000 mm x 328,000 mm	1,599,000 g (0,000 g)	3,440 Cubic dec.



product details

## OT 6/200-240/24 CE UNV1

- 1) with OPTOTRONIC dimmers
- 2) at 230 VAC
- 3) maximum at 230 V<sub>AC</sub>, P<sub>out</sub>=maximum, T<sub>a</sub>=25°C, steady state
- 4) at 100% luminous flux
- 5) at 240 V<sub>AC</sub>
- 6) max. 56 d/y at 85%