

798-289 to 393

### Van Damme 1 Pair Technical Specification

Pair conductor: 7 x 0.20mm (0.22mm sq.) 24AWG high purity OFC  
Pair insulation: Cross linked polyethylene (XLPE)  
Pair colours: 1 x white/1 x blue ~ 1.00mm diameter  
Screen: Aluminium/polyester foil tape  
Drain wire: 7 x 0.20mm (0.22mm sq.) 24AWG high purity tinned OFC  
Overall jacket: Abrasion resistant anti-kink PVC/Neoprene composite  
Jacket colour: Black ~ RAL 9005    Light green ~ RAL 6018  
Blue ~ RAL 5002    Violet ~ RAL 4008  
Red ~ RAL 3001    Orange ~ RAL 2007  
Temp.range: -25' ~ +70' Centigrade  
D.C.resistance: <78 ohms per Km  
Capacitance: <90pF per metre core to core  
<189pF per metre cores to screen  
Voltage rating: 250V  
Weight: 17Kg/Km  
O.D: 3.50mm +/-0.10mm

Construction: Twin conductors of plain (non tinned) Oxygen Free Copper with cross linked polyethylene insulation twisted together with a tinned OFC drain wire. Shielded with an aluminium/polyester foil tape. Over-sheathed with a flexible matt PVC/Neoprene outer jacket.

Stock Code	Description
798-289	1 Pair black 100m reel
798-290	1 Pair black 500m reel
798-307	1 Pair blue 100m reel
798-119	1 Pair blue 500m reel
798-320	1 Pair red 100m reel
798-332	1 Pair red 500m reel
798-344	1 Pair light green 100m reel
798-356	1 Pair light green 500m reel
798-368	1 Pair violet 100m reel
798-370	1 Pair violet 500m reel
798-381	1 Pair orange 100m reel
798-393	1 Pair orange 500m reel