

13		12		11		10		9		8		7		6		5558		4		3		2		1	
PART NO.	ENG. NO.	FORM	MAT'L.	WIRE GAGE	RANGE OF INSULATION DIA.	QUANTITY PER REEL (FORMED)	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"	DIM. "E"	DIM. "F"													
39-00-0120	5558-S	CHAIN	A	18-24 GA.	.051-.122 (1.30-3.10)	4,000	.075 (1.90)	.091 (2.30)	.020 (.50)	.142 (3.60)	.177 (4.50)	.035 (.90)													
39-00-0121	5558-SL	LOOSE			22-28 GA.	.035-.071 (.90-1.80)	6,000	.071 (1.80)	.065 (1.65)	.016 (.40)	.091 (2.30)	.091 (2.30)	.024 (.60)												
39-00-0122	5558-S2	CHAIN		16 GA.		.122 (3.10) MAX.	4,000	.091 (2.30)	.106 (2.70)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)												
39-00-0123	5558-S2L	LOOSE			14 GA.	.122 (3.10) MAX.	4,000	.091 (2.30)	.114 (2.90)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)												
39-00-0124	5558-S3	CHAIN		B		28-30 GA.	.020-.035 (.50-.90)	6,000	.050 (1.27)	.044 (1.12)	.010 (.25)	.091 (2.30)	.091 (2.30)	.024 (.60)											
39-00-0125	5558-S3L	LOOSE			18-24 GA.		.051-.122 (1.30-3.10)	4,000	.075 (1.90)	.091 (2.30)	.020 (.50)	.142 (3.60)	.177 (4.50)	.035 (.90)											
NOT TOOLED	5558-S4	CHAIN				22-28 GA.	.035-.071 (.90-1.80)	6,000	.071 (1.80)	.065 (1.65)	.016 (.40)	.091 (2.30)	.091 (2.30)	.024 (.60)											
NOT TOOLED	5558-S4L	LOOSE			16 GA.		.122 (3.10) MAX.	4,000	.091 (2.30)	.106 (2.70)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)											
39-00-0259	5558-S5	CHAIN				14 GA.	.122 (3.10) MAX.	4,000	.091 (2.30)	.114 (2.90)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)											
39-00-0260	5558-S5L	LOOSE			28-30 GA.		.020-.035 (.50-.90)	6,000	.050 (1.27)	.044 (1.12)	.010 (.25)	.091 (2.30)	.091 (2.30)	.024 (.60)											
39-00-0126	5558-PBS	CHAIN	18-24 GA.			.051-.122 (1.30-3.10)	4,000	.075 (1.90)	.091 (2.30)	.020 (.50)	.142 (3.60)	.177 (4.50)	.035 (.90)												
39-00-0127	5558-PBSL	LOOSE				22-28 GA.	.035-.071 (.90-1.80)	6,000	.071 (1.80)	.065 (1.65)	.016 (.40)	.091 (2.30)	.091 (2.30)	.024 (.60)											
39-00-0128	5558-PBS2	CHAIN	16 GA.				.122 (3.10) MAX.	4,000	.091 (2.30)	.106 (2.70)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)											
39-00-0129	5558-PBS2L	LOOSE				14 GA.	.122 (3.10) MAX.	4,000	.091 (2.30)	.114 (2.90)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)											
39-00-0130	5558-PBS3	CHAIN	28-30 GA.	.020-.035 (.50-.90)			6,000	.050 (1.27)	.044 (1.12)	.010 (.25)	.091 (2.30)	.091 (2.30)	.024 (.60)												
39-00-0131	5558-PBS3L	LOOSE		18-24 GA.		.051-.122 (1.30-3.10)	4,000	.075 (1.90)	.091 (2.30)	.020 (.50)	.142 (3.60)	.177 (4.50)	.035 (.90)												
NOT TOOLED	5558-PBS4	CHAIN				22-28 GA.	.035-.071 (.90-1.80)	6,000	.071 (1.80)	.065 (1.65)	.016 (.40)	.091 (2.30)	.091 (2.30)	.024 (.60)											
NOT TOOLED	5558-PBS4L	LOOSE		16 GA.			.122 (3.10) MAX.	4,000	.091 (2.30)	.106 (2.70)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)											
39-00-0263	5558-PBS5	CHAIN				14 GA.	.122 (3.10) MAX.	4,000	.091 (2.30)	.114 (2.90)	.024 (.60)	.142 (3.60)	.177 (4.50)	.035 (.90)											
39-00-0264	5558-PBS5L	LOOSE		28-30 GA.	.020-.035 (.50-.90)		6,000	.050 (1.27)	.044 (1.12)	.010 (.25)	.091 (2.30)	.091 (2.30)	.024 (.60)												

LEGEND:

5558-***S**

BASE NO. _____

MATERIAL _____

BLANK= BRASS

PB= PHOS. BRONZE

S= TIN OVER NICKEL _____

CRIMP SIZE _____

BLANK = 18-24 AWG

2 = 22-28 AWG

3 = 16 AWG

4 = 14 AWG

5 = 28-30 AWG

CHAIN OR LOOSE _____

BLANK= CHAIN

L= LOOSE

B	SEE SHEET I.
A2	SEE SHEET I.
A1	SEE SHEET I.
A	SEE SHEET I.

DIMENSIONS SHOWN METRIC (INCH)		UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°		TITLE		MALE CRIMP TERMINAL WITH TIN OVER NICKEL POSTPLATE (MINI-FIT JR. SERIES)		PART NO.		MOLEX INCORPORATED		SHEET NO.		DATE	
3 PLACE ± ---		METRIC		SEE CHART.		SD-5558-S*		L15LEJLL		60532		2		5/12/92	
2 PLACE ± ---		SCALE		DRAWN BY		RJV		CHKD BY		GEP		FILE NAME		5558SXX2	
1 PLACE --- ± ---		APP'D BY		RAS		SCALE		---		---		DIV.		CP	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS															
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.															