





**Led Signalleuchten Einbaudurchmesser 6 mm**  
**Led Indicators Body diameter 6 mm**

**Zweifarbige, mit Innenreflektor**  
**Duo Led, with interior reflector**

Bestell-Nr. Part No.	Farbe Colour	V <sub>OP</sub> +10% (V)	I <sub>OP max.</sub> (mA)	V <sub>F</sub> (V)	I <sub>V typ.</sub> (mcd) *I <sub>F</sub> = 20mA	I <sub>F max.</sub> (mA)	Abb. Illu.	Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No.	19030-A	A			
1903*004	Super red/ Green			2,0/2,2 2,2/2,8	*14/22	30	A		19030-A	A			
1903*005	Super red/ Yellow			2,0/2,2 2,2/2,8	*14/14	30	A						
1903*006	Green/ Yellow			2,0/2,2 2,2/2,8	*22/14	30	A						
1903*054	Super red/ Green			2,0/2,2 2,2/2,8	*14/22	30	B						
1903*055	Super red/ Yellow			2,0/2,2 2,2/2,8	*14/14	30	B						
1903*056	Green/ Yellow			2,0/2,2 2,2/2,8	*22/14	30	B						
1903*154	Super red/ Green	6	30		19/34		B					19030-A	A
1903*155	Super red/ Yellow	6	30		19/20		B						
1903*156	Green/ Yellow	6	30		34/20		B						
1903*254	Super red/ Green	12	30		19/34		B					19030-B	B
1903*255	Super red/ Yellow	12	30		19/20		B						
1903*256	Green/ Yellow	12	30		34/20		B						
1903*354	Super red/ Green	24	18		13/20		B						
1903*355	Super red/ Yellow	24	18		13/13		B						
1903*356	Green/ Yellow	24	18		20/13		B						
									19030-B	B			

Arbeitstemperatur (T<sub>OP</sub>): -55°C - +70°C  
 Lagertemperatur (T<sub>STG</sub>): -55°C - +100°C

\* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0      Schwarzchrom = 1

Beispiel:      19030004 super rot / grün mit Glanzchrom  
                  19031004 super rot / grün mit Schwarzchrom

Led Signalleuchten mit anderen Spannungen auf Anfrage  
 Technische Änderungen vorbehalten

Operating temperature (T<sub>OP</sub>): -55°C - +70°C  
 Storage temperature (T<sub>STG</sub>): -55°C - +100°C

\* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0      Black chrome = 1

Example:      19030004 super red / green with bright chrome  
                  19031004 super red / green with black chrome

Led Indicators with other voltages upon request  
 Specification subject to change without notice