

# Castors

## Nylon Wheel



68 0010:



68 0040:



### Features:

- Offers injection moulded virgin nylon 6 wheel which are available with plain and roller bearing bore.
- The wheel can be fitted in the following zinc plated pressed steel single ball race.

68 0061:



68 0202:



68 0020:



### Recommended Uses:

This wheel is recommended for standard to medium-heavy duty loads.

### Working Environment:

Manual handling applications.

Suitable for use on compact floors e.g. cement, stone tiles, metallic, epoxy resins etc.

Particularly recommended for the food processing industry. Not recommended for use with concentrated organic acids or strong mineral acids.

### Specifications:

Temperature : -30°C to +80°C for nylon 6 but capacity should be down rated below -10°C and above +60°C.

### Specification Table

Description	Wheel Diameter	Thread Width	Overall Height	Plate Dimension	Ball Race	Hole Spacing	Hole Width	Offset	Carrying Capacity (kg)	Part Number
Castor, Nylon Wheel, Swivel	50	19	64	67 x 48	1	54/56 x 25	6	13	40	68 0010
Castor, Nylon Wheel, Swivel	63	23	78	95 x 70		73/76 x 44.5	8	20	85	68 0040
Castor, Nylon Wheel, Swivel	75	25	94	105 x 80		80/86 x 60		22	120	68 0061
Castor, Nylon Wheel, Swivel	100	32	125	128 x 102		100/105 x 76/80	10	25	225	68 0202

Dimensions : Millimetres



# Castors

## Nylon Wheel



### Specification Table

Description	Wheel Diameter	Thread Width	Overall Height	Plate Dimension	Hole Spacing	Hole Width	Carrying Capacity (kg)	Part Number
Standard Duty, Castor, Nylon Wheel, Fixed	50	19	64	69 x 44	54/56 x25	6	40	68 0020

Dimensions : Millimetres

**Disclaimer** This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2009.

<http://www.farnell.com>  
<http://www.newark.com>  
<http://www.cpc.co.uk>

