


NOTES: UNLESS OTHERWISE SPECIFIED

1. BODIES: BRASS PER JIS-C3604
2. CENTER CONTACT: BERYLLIUM COPPER PER JIS-C1730B
3. INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710
4. CONNECTOR INTERFACE PER MIL-STD-348A
5. PART TO BE CLEAN AND FREE OF BURRS

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
3	INSULATION	TEFLON	1	NONE
2	CENTER CONTACT	BERYLLIUM COPPER	1	GOLD 50 μ " MIN.
1	BODY	BRASS	1	GOLD 3 μ " MIN.

製圖	DRAWN	TOLERANCE		品名	DWG.NO.	DATE	版次	REV.
	梁齡允	.X	± 0.2	19-46-2 (50 Ω)		07.25.02	A-0	
檢圖	CHECK	.XX	± 0.1	單位	19-0096	 佳楠精密電子股份有限公司 CHIN NAN PRECISION ELECTRONICS CO.,LTD.		
	沈淑美	.XXX	± 0.05	mm(in)				
認定	APPROVAL	余賢德	ANGLE $\pm 5^\circ$	比例	6:1			