

RECOMMENDED PCB LAYOUT

TOLERANCE:

DIMENSIONS	ANGLES
X. = ±0.25mm	±2.0°
X.X = ±0.15mm	±1.0°
X.XX = ±0.10mm	±0.5°

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES	MATERIAL:	TITLE:
X. = ±1mm	SEE NOTES	PITCH 2.4mm HEIGHT 5.0mm
X.X = ±0.25mm		2-POS POGO PIN CONNECTOR
X.XX = ±0.10mm		
X.XXX = ±0.01mm		
ANGLES = ±5°		
UNLESS STATED		

FINISH: SEE NOTES

S/AREA: mm²

DRAWING NUMBER:
P20-0245R

SHT
1
OF
1

SPECIFICATIONS:

MATERIAL:-

HOUSING: BLACK PA9T (UL94V-0)

PLUNGER & BARREL: BRASS

SPRING: SWP Au PLATED

FINISH:-

CONTACT SURFACE: TIN/GOLD PLATED
OVER NICKEL UNDERPLATE

SPRING: Au PLATED

ELECTRICAL:-

CURRENT RATING: 1 AMP

WORKING VOLTAGE: DC 12 V

CONTACT RESISTANCE: 50 mΩ MAX AT WORKING HT

MECHANICAL:-

DURABILITY: 10 000 CYCLES MINIMUM

UNLOADED HT: 5.0mm

WORKING HT: 3.9mm

SPRING FORCE: 110g ±20% AT WORKING HT

NOTES: ALL DIMENSIONS AND NOTES
MARKED ***** ARE CRITICAL AND
MUST BE CHECKED IN ACCORDANCE
WITH QUALITY DOC. Q1-02A

Allan	1	01.08.06	-
NAME	ISS.	DATE	C/NOTE

APPROVED: *[Signature]*CHECKED: *[Signature]*

DRAWN: Allan

CUSTOMER REF.:

ASSEMBLY DRG: