


## Dual 1 Form A Solid State Relay



### FEATURES

- Dual channel (LH1500)
- Current limit protection
- Isolation test voltage 5300 V<sub>RMS</sub>
- Typical R<sub>ON</sub> 20 Ω
- Load voltage 350 V
- Load current 150 mA
- High surge capability
- Clean bounce free switching
- Low power consumption
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



**RoHS**  
COMPLIANT

### DESCRIPTION

The LH1520 dual 1 form A relays are SPST normally open switches that can replace electromechanical relays in many applications. They are constructed using a GaAlAs LED for actuation control and an integrated monolithic die for the switch output. The die, fabricated in a high-voltage dielectrically isolated technology is comprised of a photodiode array, switch control circuitry, and MOSFET switches. In addition, the LH1520 SSRs employ current limiting circuitry, enabling them to pass FCC 68.302 and other regulatory surge requirements when overvoltage protection is provided.

### APPLICATIONS

- General telecom switching
  - On/off hook control
  - Ring delay
  - Dial pulse
  - Ground start
  - Ground fault protection
- Instrumentation
- Industrial controls

### AGENCY APPROVALS

- UL1577: file no. E52744 system code H or J, double protection
- CSA: certification no. 093751
- BSI/BABT: certification no. 7980
- DIN EN: 60747-5-5 (VDE 0884)
- FIMKO: approval

ORDER INFORMATION		
PART	REMARKS	PACKAGE
LH1520AAC	Tubes	SMD-8
LH1520AACTR	Tape and reel	SMD-8
LH1520AB	Tubes	DIP-8

ABSOLUTE MAXIMUM RATINGS <sup>(1)</sup>				
PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
<b>SSR</b>				
LED continuous forward current		I <sub>F</sub>	50	mA
LED reverse voltage	I <sub>R</sub> ≤ 10 μA	V <sub>R</sub>	8.0	V
DC or peak AC load voltage	I <sub>L</sub> ≤ 50 μA	V <sub>L</sub>	350	V
Continuous DC load current, one pole operating		I <sub>L</sub>	150	mA



# LH1520AB/LH1520AAC/LH1520AACTR

Dual 1 Form A Solid State Relay Vishay Semiconductors

ABSOLUTE MAXIMUM RATINGS <sup>(1)</sup>				
PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
<b>SSR</b>				
Continuous DC load current, two poles operating		$I_L$	110	mA
Peak load current (single shot), form B	$t = 100 \text{ ms}$	$I_P$	<sup>(3)</sup>	
Ambient temperature range		$T_{amb}$	- 40 to + 85	°C
Storage temperature range		$T_{stg}$	- 40 to + 150	°C
Pin soldering temperature <sup>(4)</sup>	$t = 10 \text{ s max.}$	$T_{sld}$	260	°C
Input to output isolation test voltage	$t = 1.0 \text{ s, } I_{ISO} = 10 \text{ } \mu\text{A max.}$	$V_{ISO}$	5300	$V_{RMS}$
Pole-to-pole isolation voltage (S1 to S2) <sup>(2)</sup> (dry air, dust free, at sea level)			1600	V
Output power dissipation (continuous)		$P_{diss}$	600	mW

### Notes

- <sup>(1)</sup>  $T_{amb} = 25 \text{ } ^\circ\text{C}$ , unless otherwise specified.  
Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.
- <sup>(2)</sup> Breakdown occurs between the output pins external to the package.
- <sup>(3)</sup> Refer to current limit performance application note for a discussion on relay operation during transient currents.
- <sup>(4)</sup> Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).

ELECTRICAL CHARACTERISTICS						
PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
<b>INPUT</b>						
LED forward current, switch turn-on	$I_L = 100 \text{ mA, } t = 10 \text{ ms}$	$I_{Fon}$		1.0	2.0	mA
LED forward current, switch turn-off	$V_L = \pm 300 \text{ V}$	$I_{Foff}$	0.2	1.1		mA
LED forward voltage	$I_F = 10 \text{ mA}$	$V_F$	1.15	1.26	1.45	V
<b>OUTPUT</b>						
On-resistance	$I_F = 5.0 \text{ mA, } I_L = 50 \text{ mA}$	$R_{ON}$	12	20	25	$\Omega$
Off-resistance	$I_F = 0 \text{ mA, } V_L = \pm 100 \text{ V}$	$R_{OFF}$	0.5	300		$G\Omega$
Current limit	$I_F = 5.0 \text{ mA, } t = 5.0 \text{ ms, } V_L = \pm 6.0 \text{ V}$	$I_{LMT}$	230	270	370	mA
Off-state leakage current	$I_F = 0 \text{ mA, } V_L = \pm 100 \text{ V}$	$I_O$		0.32	200	nA
	$I_F = 0 \text{ mA, } V_L = \pm 350 \text{ V}$	$I_O$			1.0	$\mu\text{A}$
Output capacitance	$I_F = 0 \text{ mA, } V_L = 1.0 \text{ V}$	$C_O$		55		pF
	$I_F = 0 \text{ mA, } V_L = 50 \text{ V}$	$C_O$		10		pF
Pole-to-pole capacitance (S1 to S2)	$I_F = 5.0 \text{ mA}$			0.5		pF
Switch offset	$I_F = 5.0 \text{ mA}$	$V_{OS}$		0.15		$\mu\text{V}$
<b>TRANSFER</b>						
Capacitance (input to output)	$V_{ISO} = 1.0 \text{ V}$	$C_{IO}$		1.1		pF
Turn-on time	$I_F = 5.0 \text{ mA, } I_L = 50 \text{ mA}$	$t_{on}$		1.4	2.0	ms
Turn-off time	$I_F = 5.0 \text{ mA, } I_L = 50 \text{ mA}$	$t_{off}$		0.7	2.0	ms

### Note

$T_{amb} = 25 \text{ } ^\circ\text{C}$ , unless otherwise specified.  
Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluations. Typical values are for information only and are not part of the testing requirements.

## TYPICAL CHARACTERISTICS

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified




Fig. 1 - Recommended Operating Conditions




Fig. 4 - LED Reverse Current vs. LED Reverse Voltage




Fig. 2 - LED Voltage vs. Temperature




Fig. 5 - LED Current for Switch Turn-on vs. Temperature




Fig. 3 - LED Forward Current vs. LED Forward Voltage






Fig. 6 - LED Dropout Voltage vs. Temperature




ih1520ab\_06

Fig. 7 - Current Limit vs. Temperature




ih1520ab\_09

Fig. 10 - Variation in On-resistance vs. LED Current




ih1520ab\_07

Fig. 8 - Load Current vs. Load Voltage




ih1520ab\_10

Fig. 11 - Switch Capacitance vs. Applied Voltage




ih1520ab\_08

Fig. 9 - On-Resistance vs. Temperature




ih1520ab\_11

Fig. 12 - Insertion Loss vs. Frequency




ih1520ab\_12

Fig. 13 - Leakage Current vs. Applied Voltage




ih1520ab\_15

Fig. 16 - Switch Breakdown Voltage vs. Temperature




ih1520ab\_13

Fig. 14 - Output Isolation




ih1520ab\_16

Fig. 17 - Switch Offset Voltage vs. Temperature



ih1520ab\_14

Fig. 15 - Switch Breakdown Voltage vs. Load Current



ih1520ab\_17

Fig. 18 - Switch Offset Voltage vs. LED Current




Fig. 19 - Turn-on Time vs. Temperature




Fig. 22 - Turn-off Time vs. LED Current




Fig. 20 - Turn-off Time vs. Temperature




Fig. 21 - Turn-on Time vs. LED Current


# LH1520AB/LH1520AAC/LH1520AACTR



Vishay Semiconductors Dual 1 Form A Solid State Relay


## PACKAGE DIMENSIONS in inches (millimeters)

DIP



i178008

SMD



i178009



## OZONE DEPLETING SUBSTANCES POLICY STATEMENT

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively.
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA.
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design  
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany





## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.