



SPECIAL ELECTRONIC PLIERS EUROline-Conductive

Box joint

Double leaf spring

High quality steel

Fine polished and bright burnished, for dazzle free working


Ergonomically formed bicoloured hand-guard from

conductive anti-slide material

The pliers of this program have been tested with good results by several testing laboratories adequate to **DIN EN 61340-5-1, 61340-2-1, 61340-2-3** for work in ESD protected areas



3-651-15




3-651-15 DR



3-652-15




3-653-15



3-654-15



3-656-15



3-671-15



3-672-15



3-673-15



3-674-15



3-675-15

CUTTING PLIERS

No.	Length		Finish	cutting capacity mm Ø			Weight g
	mm	inches		Copper-wire	Soft wire	Hard wire	

Mini side cutters EUROline-Conductive

with very slim, rounded head for finest operations

3-651-15	120	4 3/4	without side face	1.2	0.6	-	55
3-651-15 DR	120	4 3/4	without side face, with retaining spring	1.2	0.6	-	55

Mini side cutters EUROline-Conductive

with very slim, pointed head for finest operations

3-652-15	120	4 3/4	without side face	1.0	0.6	-	55
3-653-15	120	4 3/4	without side face, with special flat cutting edge	1.0	0.6	-	55

Side cutters EUROline-Conductive

with slim, rounded head, available with or without side face

3-654-15	125	5	with side face	1.5	1.0	0.4	60
3-655-15	125	5	without side face	1.5	1.0	-	60

Side cutters EUROline-Conductive

with slim, pointed head, available with or without side face

3-656-15	125	5	with side face	1.2	1.0	0.4	60
3-657-15	125	5	without side face	1.2	1.0	-	60

End cutters EUROline-Conductive

extremely slim, without side face, for precision work at points difficult to reach

3-671-15	130	5 1/8	straight	0.6	-	-	60
3-672-15	130	5 1/8	cutting edge 20° angular	0.6	-	-	60

Top cutters EUROline-Conductive

extremely slim, without side face, head 45° angular, for flush cutting directly in front of and behind the components.

3-673-15	130	5 1/8	cutting edge inside	0.6	-	-	60
3-674-15	130	5 1/8	cutting edge outside	0.6	-	-	60

Oblique top cutters EUROline-Conductive

cutting plane 29° angular, flush cutting for horizontal and vertical use

3-675-15	115	4 1/2	without side face	1.2	1.0	0.4	65
----------	-----	-------	--------------------------	-----	-----	-----	----