

Part Number: SL12 15004

### Ordering Different Lead Types:

Inside Kinked Leads	Use <b>-A</b> after Ametherm's part #
Outside Kinked Leads	Use <b>-B</b> after Ametherm's part #

For example: to order an inside kinked lead use part number SL12 15004-A



### Electrical Specifications:

Resistance @ 25°C	15.0 $\Omega$ $\pm$ 15%
Max Steady State Current Up to 65°C	4.0 A
Max Recommended Energy Rating (Joules)	40.0 J
Actual Failure Point of Instantaneous Energy (Joules)	105.0 J
Resistance @ 100% of Max Current	0.160 $\Omega$
Resistance @ 50% of Max Current	0.338 $\Omega$
Body Temperature @ 100% Current Rating	152 °C
Dissipation Constant	13.9mW/°C
Thermal Time Constant	54 seconds
Material Type	"C"
Max Recommended Capacitance @ 120VAC/240VAC	2700 $\mu$ F/690 $\mu$ F

### Mechanical Specifications:

D	12.0 $\pm$ 0.5 mm
T	5.5 $\pm$ 0.5 mm
Lead Diameter	0.80 $\pm$ 0.1 mm
S	7.8 $\pm$ 2.0 mm
L	20.0 $\pm$ 1.5 mm
Straight Leads	See Dimension
Coating Run Down	B below
B	5.10 mm Max
C	2.82 $\pm$ 0.5 mm